Adaptadores de bridas de PP-RCT de Uponor (fusión de toma)

Project information


Job name:	Location:
Engineer:	Fecha de envío:
Contractor:	Presentada por:
Manufacturer's representative:	Approved by:

Technical data

Material	PP-RCT
End type 2	Flange
	180 °F (82 °C) at 100 psi (6.9 bar)

Product information and application use

Use Uponor PP-RCT flange adapters with Uponor PP-RCT mechanical pipe to convey water for hydronic heating and cooling or industrial applications.



	Part name	Part no.	End Type 1
	Uponor PP-RCT Flange Adapter, 1	PR2981000	Socket 1"
	Uponor PP-RCT Flange Adapter, 1 1/4	PR2981250	Socket 1-1/4"
	Uponor PP-RCT Flange Adapter, 1 1/2	PR2981500	Socket 1-1/2"
	Uponor PP-RCT Flange Adapter, 2	PR2982000	Socket 2"
✔	Uponor PP-RCT Flange Adapter, 2 1/2	PR2982525	Socket 2-1/2"
	Uponor PP-RCT Flange Adapter, 3	PR2983030	Socket 3"

Part name	Part no.	Codes	Standards	Listings
Adaptadores de bridas de PP-RCT de Uponor (fusión de toma)	All	UPC|IRC|IPC|NPC of Canada|UMC|CMC|CPC|IMC	NSF/ANSI/CAN 61|ASTM E84|NSF/ANSI 14|NSF/ANSI 51|ASTM F2389|CSA B137.11	ICC-ES-PMG 1106|IAPMO-R&T 8358|QAI P321-5|IAPMO K-12775

Installation

Use approved socket-fusion connection methods. Refer to the Uponor PP-RCT manual for complete details.

Related applications

Hydronic heating and cooling systems

Industrial

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517

© 2024 Uponor North America. All Rights Reserved