Adaptadores con rosca macho TotalFit

Project information


Job name:	Location:
Engineer:	Fecha de envío:
Contractor:	Presentada por:
Manufacturer's representative:	Approved by:

Technical data

Material	Engineered Polymer
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)
Prop 65 label required?	No

Product information and application use

TotalFit™ is the professional-grade engineered polymer (EP) push-to-connect solution that provides greater value for residential projects with the same versatility and speed as brass push-to-connect fittings for PEX, PE-RT, CPVC, and copper piping systems.



	Part name	Part no.	End Type 1	End Type 2
	TotalFit Male Threaded Adapter, 1" x 1" NPT	TF4521010	TotalFit 1"	MNPT 1"
	TotalFit Male Threaded Adapter, 1/2" x 1/2" NPT	TF4525050	TotalFit 1/2"	MNPT 1/2"
	TotalFit Male Threaded Adapter, 1/2" x 3/4" NPT	TF4525075	TotalFit 1/2"	MNPT 3/4"
	TotalFit Male Threaded Adapter, 3/4" x 1" NPT	TF4527510	TotalFit 3/4"	MNPT 1"
✔	TotalFit Male Threaded Adapter, 3/4" x 3/4" NPT	TF4527575	TotalFit 3/4"	MNPT 3/4"

Part name	Part no.	Codes	Standards	Listings
Adaptadores con rosca macho TotalFit	All	UPC|IRC|IPC|NPC of Canada|UMC|CMC|CPC|IMC	ASTM F877|NSF/ANSI/CAN 372|NSF/ANSI/CAN 61|NSF/ANSI 14|ASSE 1061	IAPMO K-13573|IAPMO K-13571|IAPMO K-13572
In addition, the following parts have additional codes, standards, or listings:				
TotalFit Male Threaded Adapter, 1/2" x 1/2" NPT	TF4525050			
TotalFit Male Threaded Adapter, 3/4" x 3/4" NPT	TF4527575			

Installation

Install on PEX, PE-RT, CPVC, and copper piping systems. Use deburr and depth tool to remove excess material or burrs and mark the appropriate depth on pipe. If using flexible PEX or PE-RT, install the insert inside the pipe first before making the connection. Only use PTFE thread seal tape (with a minimum of three wraps) to seal male and female adapters. Refer to the Uponor TotalFit Instruction Sheet for additional information.

Related applications

Plumbing

Hydronic Heating & Cooling

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517

© 2024 Uponor North America. All Rights Reserved