

# Accesorios para colectores con válvula de cobre: adaptador de cobre de válvulas de bola y compensación



## Project Information

Job name:	Location:
Engineer:	Fecha de envío:
Contractor:	Presentada por:
Manufacturer's representative:	Approved by:

## Technical data

Material	Brass
Subcomponent Material	CA 360 Brass
End type 1	ISO 228-G 3/4"
End type 2	Sweat 3/4"
Cold working pressure	246.6 psi
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)
Prop 65 label required?	Yes



## Product information and application use

The Uponor Ball and Balancing Valves include 3/4" copper adapters and feature in-line isolation valves.

Part name	Part no.	Codes	Standards	Listings
Accesorios para colectores con válvula de cobre: adaptador de cobre de válvulas de bola y compensación	A5902075	-	CSA B125 ASME A112.18.1	-

## Installation

Install valve according to local building code. Do not dismantle. If soldering, aim flame away from fitting. For more information, refer to the AquaPEX® Professional Plumbing Installation Guide or Radiant Floor Installation Handbook.

## Related applications

- PEX-a Plumbing Systems
- Radiant Heating and Cooling Systems
- Permafrost Protection Systems
- Turf Conditioning Systems

## Footnotes

-

## Contact information

Uponor Inc.  
5925 148th Street West  
Apple Valley, MN 55124  
T 800.321.4739  
F 952.891.2008

Uponor Ltd.  
6510 Kennedy Road  
Mississauga, ON L5T 2X4  
T 888.594.7726  
F 800.638.9517