# Cajas para equipos para fabricar hielo de bronce sin plomo (LF) ProPEX

## Project information

| | |
|---|---|
| Job name: | Location: |
| Engineer: | Fecha de envío: |
| Contractor: | Presentada por: |
| Manufacturer's representative: | Approved by: |

## Technical data

| | |
|---|---|
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar)<br>180 °F (82 °C) at 100 psi (6.9 bar)<br>200 °F (93 °C) at 80 psi (5.5 bar) |

## Product information and application use

The ProPEX® Ice Maker Box with Support Brackets, ½" (LF Brass) Valve with snap-in frame includes a ½" lead-free brass valve with ¼" O.D. compression connection. This high-impact box is an aesthetic, convenient option for connecting to standard ice maker tubing. Two support brackets are provided for easy mounting.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.



| Part name | Part no. | A [inch] | B [inch] | C [inch] | Material group | End Type 1 | End Type 2 | Prop 65 label required? | Weight per UOM [lbs/UOM] |
|---|---|---|---|---|---|---|---|---|---|
| ProPEX Ice Maker Box with Support Brackets, 1/2" LF Brass Valve | LF5955025 | 20.29 | 6 | 3.55 | - | ProPEX | Compression | Yes | 0.87 |
| 1/4" Insert (stainless steel) | F5400250 | 0.719 | 0.323 | 0.323 | Stainless Steel | - | - | - | 0 |

| Part name | Part no. | Codes | Standards | Listings |
|---|---|---|---|---|
| Cajas para equipos para fabricar hielo de bronce sin plomo (LF) ProPEX | All | UPC\|IPC\|NPC of Canada | NSF-372\|ASME A112.18.1\|ASTM F877\|ASTM F1960\|CSA B125\|CSA B137.5\|NSF-61\|NSF-14 | cNSFus-pw-G\|U.P.Code |

## Installation

Mount in wall cavity at the desired location (e.g., behind refrigerator) using the supplied mounting brackets or directly to studs. For more information, refer to the AquaPEX® Professional Plumbing Installation Guide.

## Related applications

PEX-a Plumbing Systems

## Footnotes

-

## Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517

© 2024 Uponor North America. All Rights Reserved