

Conectores en T para equipos para fabricar hielo de bronce sin plomo (LF) ProPEX



Project Information

| | |
|--------------------------------|-----------------|
| Job name: | Location: |
| Engineer: | Fecha de envío: |
| Contractor: | Presentada por: |
| Manufacturer's representative: | Approved by: |

Technical data

| | |
|-------------------------|-------------------------------------|
| Material | LF Brass |
| End type 1 | ProPEX 1/2" |
| End type 2 | ProPEX 1/2" |
| End type 3 | Compression 1/4" |
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar) |
| | 180 °F (82 °C) at 100 psi (6.9 bar) |
| | 200 °F (93 °C) at 80 psi (5.5 bar) |
| Prop 65 label required? | Yes |



Product information and application use

Approved for hot and cold potable water systems, the ProPEX® Leadfree Brass In-line Ice Maker Tee provides quick, safe, water-line connections for an in-line ice maker. Use with 1/2" PEX tubing. The valve features 3/8" NPT x 1/4" O.D. compression.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.

| Part name | Part no. | A [inch] | B [inch] | C [inch] | Weight per UOM [lbs/UOM] |
|--|-----------|----------|----------|----------|--------------------------|
| ProPEX LF Brass In-line Ice Maker Tee, 1/2" PEX x 1/2" PEX x 1/4" O.D. compression | LF4455050 | 2.517 | 2.369 | 1.652 | 0.3 |

| Part name | Part no. | Codes | Standards | Listings |
|--|-----------|--|--|----------------------|
| Conectores en T para equipos para fabricar hielo de bronce sin plomo (LF) ProPEX | LF4455050 | UPC IBC IRC IPC NPC of Canada UMC NSPC IMC | NSF/ANSI/CAN 372 ASTM F877 ASTM F1960 CSA B137.5 NSF/ANSI/CAN 61 NSF/ANSI 14 | cNSFus-pw-G U.P.Code |

Installation

ProPEX Tool and ProPEX Rings (sold separately) are required for connecting the PEX tubing. For more information, refer to the AquaPEX® Professional Plumbing Installation Guide.

Related applications

PEX-a Plumbing Systems

Footnotes

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517