
# Adaptadores y bujes rectos para colectores de bronce con rosca

## Project information

| | |
|---|---|
| Job name: | Location: |
| Engineer: | Fecha de envío: |
| Contractor: | Presentada por: |
| Manufacturer's representative: | Approved by: |

## Technical data

| | |
|---|---|
| Material | Brass |
| End type 1 | ISO 228-G 1-1/4" |
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar)<br>180 °F (82 °C) at 100 psi (6.9 bar)<br>200 °F (93 °C) at 80 psi (5.5 bar) |
| Prop 65 label required? | Yes |




## Product information and application use

Uponor's Threaded Brass Manifold Bushings are used in TruFLOW™ manifolds. In radiant heating applications, the bushing transitions the R32 manifold union nut to 1" national pipe thread (NPT) and ¾" threaded connections (PEX or Multi-layer Composite (MLC) tubing with QS-style fittings).

| Part name | Part no. | A [inch] | B [inch] | C [inch] | End Type 2 | Weight per UOM [lbs/UOM] |
|---|---|---|---|---|---|---|
| Threaded Brass Manifold Bushing, R32 Male x 3/4" Female NPT | A2133275 | 2.018 | 1.75 | 0.985 | FNPT 3/4" | 0.44 |
| Threaded Brass Manifold Bushing, R32 Male x 1" Female NPT | A2123210 | 1.918 | 1.687 | 0.985 | FNPT 1" | 0.3 |

| Part name | Part no. | Codes | Standards | Listings |
|---|---|---|---|---|
| Adaptadores y bujes rectos para colectores de bronce con rosca | All | IMC\|IRC\|NBC of Canada\|UMC | CSA B137.5\|R32: ISO 228-G 1¼"\|ASTM F877 | cNSFus-rfh |

## Installation

Thread directly into Uponor TruFLOW manifolds. For additional information, refer to the TruFLOW Manifold Instruction Sheet or the Uponor Radiant Floor Heating Installation Handbook.

## Related applications

Radiant Heating and Cooling Systems

Permafrost Protection Systems

Turf Conditioning Systems

## Footnotes

-

## Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517

© 2026 Uponor North America. All Rights Reserved