

Colectores sin válvula de cobre y con conexiones ProPEX

Project information

| | |
|--------------------------------|-----------------|
| Job name: | Location: |
| Engineer: | Fecha de envío: |
| Contractor: | Presentada por: |
| Manufacturer's representative: | Approved by: |

Technical data

| | |
|-------------------------|--------------------------------------|
| Material | Copper |
| Manifold size | 2 inch |
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar) |
| | 180 °F (82 °C) at 100 psi (6.9 bar) |
| | 200 °F (93 °C) at 80 psi (5.5 bar) |
| | 210 °F (99 °C) at 149 psi (10.3 bar) |
| Max. fluid flow rate | 45 gpm |
| Prop 65 label required? | Yes |



Product information and application use

The 2" Copper Valveless Manifold with ProPEX® Connection is used for radiant heating projects. The manifold has a 2" copper sweat fitting adapter supply connection and 3/4" nominal branches. This 12-outlet manifold is preassembled with 5/8" or 3/4" ProPEX connections.

This product is made to order, please contact [customer service](#) for lead time.

| Part name | Part no. | End Type 1 |
|----------------------------------------------------------------|----------|-------------|
| 2" x 4' Copper Valveless Manifold with 5/8" ProPEX, 12 outlets | Q2831263 | ProPEX 5/8" |
| 2" x 4' Copper Valveless Manifold with 3/4" ProPEX, 12 outlets | Q2831275 | ProPEX 3/4" |

| Part name | Part no. | Codes | Standards | Listings |
|---------------------------------------------------------|----------|-------|----------------------|------------|
| Colectores sin válvula de cobre y con conexiones ProPEX | All | - | CSA B137.5 ASTM F877 | cNSFus-rfh |

| Installation | Related applications |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|
| Any product designed to mount 2" copper pipe may be used as a mounting bracket. Refer to the Uponor Radiant Installation Handbook for additional information. Accessories: 2" Copper Manifold End Cap (A2402000). | Radiant Heating and Cooling Systems |

| Footnotes | Contact information |
|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| - | <div>Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008</div> <div>Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517</div> |