Colectores de cobre (tipo L) sin plomo (LF) ProPEX

Project information

Job name:	Location:
Engineer:	Fecha de envío:
Contractor:	Presentada por:
Manufacturer's representative:	Approved by:

Product information and application use

Uponor's 1" Copper Manifold is 6 feet in length and features 24 individual ½" ProPEX® lead-free brass outlets spaced three inches on center. The manifold is suitable for cutting to any length necessary to achieve the desired number of outlets. ProPEX Tool is required. ProPEX Rings are sold separately.

This product is made to order, please contact customer service for lead time.



Installation

Any product designed to mount 1" copper pipe may be used as a mounting bracket. Any bend within 6 inches of the ProPEX connection to the manifold requires the use of a Tube Talon (F7050750) or Bend Support (A5110500 and A5150500). Refer to the AquaPEX® Professional Plumbing Installation Guide or the Radiant Floor Heating Installation Handbook for additional information.

Related applications

PEX-a Plumbing Systems

Radiant Heating and Cooling Systems

Permafrost Protection Systems

Turf Conditioning Systems

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517

© 2024 Uponor North America. All Rights Reserved