
Codos multipuerto en ramal de EP para aplicaciones comerciales

Project information

Job name:	Location:
Engineer:	Fecha de envío:
Contractor:	Presentada por:
Manufacturer's representative:	Approved by:

Technical data

Material	Engineered Polymer
End type 2	ProPEX 1/2"
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar)
	180 °F (82 °C) at 100 psi (6.9 bar)
	200 °F (93 °C) at 80 psi (5.5 bar)



Product information and application use

Engineered polymer (EP) branch multi-port elbows feature an integrated ¾" or 1" ProPEX® inlet with ½" ProPEX branch outlets. The elbows are designed for commercial plumbing applications to eliminate the need for multiple connections. Product includes EP Mounting Clips (F7051250) with Phillips self-tapping screws.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.

Part name	Part no.	A [inch]	B [inch]	C [inch]	D [inch]	E [inch]	F [inch]	G [inch]	H [inch]	I [inch]	J [inch]
3/4" EP Branch Multi-port Elbow, 8 (1/2") outlets with mounting clips	Q2087550	9.89	2.325	1.768	0.685	1.2	0.9	0.59	0.685	0.65	0.719
1" EP Branch Multi-port Elbow, 10 (1/2") outlets with mounting clips	Q2101000	11.75	2.561	1.768	0.685	1.2	0.9	0.75	0.685	0.65	0.719

Part name	Part no.	End Type 1	Weight per UOM [lbs/UOM]
3/4" EP Branch Multi-port Elbow, 8 (1/2") outlets with mounting clips	Q2087550	ProPEX 3/4"	0.39
1" EP Branch Multi-port Elbow, 10 (1/2") outlets with mounting clips	Q2101000	ProPEX 1"	0.47

Part name	Part no.	Codes	Standards	Listings
Codos multipuerto en ramal de EP para aplicaciones comerciales	All	UPC|IMC|IPC|IBC|IRC|UMC|NSPC|NPC of Canada	ASTM E119/UL 263|ASTM F1960|ASTM E814/ULC S115|CSA B137.5|NSF/ANSI 14|NSF/ANSI/CAN 61|ASTM F877|ULC S102.2|ULC S101	cNSFus-pw|IAPMO-ES|ICC-ES-PMG|cQAIus P321|UL|U.P.Code|HUD MR 1269

Installation

The mounting clips feature self-tapping screws, which are appropriate for wood or metal studs. Simply attach the clips to the multi-port and fasten the clips to the mounting surface.

Related applications

PEX-a Plumbing Systems

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517

© 2026 Uponor North America. All Rights Reserved