υροποι

Joist Trak

Project information	
Job name:	Location:
Engineer:	Fecha de envío:
Contractor:	Presentada por:
Manufacturer's representative:	Approved by:

Technical data		
Material	Aluminum	
Subcomponent Material	16-gauge aluminum	
Prop 65 label required?	Yes	
Product information and application use		

Product information and application use

Use Joist TrakTM extruded aluminum heat transfer panels with $\frac{3}{6}$ " or $\frac{1}{2}$ " Uponor PEX in floor joist applications. Each panel is 4 feet long by $3\frac{1}{2}$ inches wide, and comes packaged 20 per box. It provides easy installation, increased heat transfer and superior comfort.



Installation

Using the pre-punched mounting holes, install the panels with either screws or nails. Leave a minimum $^{1}\!\!/_{4}^{*}$ gap between plates to allow for expansion. Simply snap the tubing into the channel of the Joist Trak panel. Refer to the Uponor Joist Trak Heat Transfer Panel Installation Handbook for additional information.

Related applications

Radiant Heating and Cooling Systems

Footnotes	Contact information	
	Uponor Inc.	Uponor Ltd.
	5925 148th Street West	6510 Kennedy Road
-	Apple Valley, MN 55124	Mississauga, ON L5T 2X4
	T 800.321.4739	T 888.594.7726
	F 952.891.2008	F 800.638.9517