

Joist Trak

Project information

Job name:	Location:
Engineer:	Fecha de envío:
Contractor:	Presentada por:
Manufacturer's representative:	Approved by:

Technical data

Material	Aluminum
Subcomponent Material	16-gauge aluminum
Prop 65 label required?	Yes

Product information and application use

Use Joist Trak™ extruded aluminum heat transfer panels with 3⁄8" or 1⁄2" Uponor PEX in floor joist applications. Each panel is 4 feet long by 3½ inches wide, and comes packaged 20 per box. It provides easy installation, increased heat transfer and superior comfort.



Part name	Part no.	A [Inch]	B [Inch]	C [Inch]	Weight per UOM [lbs/UOM]
Joist Trak, 3/8" Heat Transfer Panel	A5080375	48	3.5	0.546	-
Joist Trak, 1/2" Heat Transfer Panel	A5080500	48	3.5	0.675	-

Installation	Related applications
Using the pre-punched mounting holes, install the panels with either screws or nails. Leave a minimum 1⁄4" gap between plates to allow for expansion. Simply snap the tubing into the channel of the Joist Trak panel. Refer to the Uponor Joist Trak Heat Transfer Panel Installation Handbook for additional information.	Radiant Heating and Cooling Systems

Footnotes	Contact information
-	<div>Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008</div> <div>Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517</div>