

# Ensamblaje de colectores de acero inoxidable comercial de 1 1/2 in con caudalímetro y válvula de bola




## Project Information

Job name:	Location:
Engineer:	Fecha de envío:
Contractor:	Presentada por:
Manufacturer's representative:	Approved by:

## Technical data

Material	Stainless Steel
Manifold size	2 inch
End type 1	FNPT 1-1/2"
End type 2	ISO 228-G 1"
Temp/pressure ratings	68 °F (20 °C) at 145 psi (10 bar) 158 °F (70 °C) at 87 psi (6 bar) 194 °F (90 °C) at 44 psi (3 bar)
Max. fluid flow rate	48 gpm
Prop 65 label required?	Yes



## Product information and application use

The Uponor Commercial Stainless-steel Manifold is used for distribution and loop isolation in hydronic hot-water heating, chilled water, and radiant heating and cooling applications. The manifold features 1-1/2" distribution ball valves with 1" isolation ball valves on the supply manifold for easy loop isolation along with flow meters on the return manifold to balance the loops from 0-4 gpm. The R25 connections for outlet fittings are sold separately and are available in 5/8" and 3/4" compression or 5/8", 3/4", and 1" ProPEX.

Part name	Part no.	Codes	Standards	Listings
Ensamblaje de colectores de acero inoxidable comercial de 1 1/2 in con caudalímetro y válvula de bola	All	-	-	-

## Installation

Refer to the Uponor Commercial Stainless-steel Manifold Instruction Sheet for installation guidelines.

## Related applications

- Radiant Heating and Cooling Systems
- Snow and Ice Melting Systems
- Permafrost Protection Systems
- Turf Conditioning Systems

## Footnotes

-

## Contact information

Uponor Inc.  
5925 148th Street West  
Apple Valley, MN 55124  
T 800.321.4739  
F 952.891.2008

Uponor Ltd.  
6510 Kennedy Road  
Mississauga, ON L5T 2X4  
T 888.594.7726  
F 800.638.9517