# Módulo de comunicación Smatrix Pulse (R-208), piezas de reemplazo

## Project information


| | |
|---|---|
| Job name: | Location: |
| Engineer: | Fecha de envío: |
| Contractor: | Presentada por: |
| Manufacturer's representative: | Approved by: |

## Technical data

| | |
|---|---|
| Operating temperature min. [°F] | 32 °f |
| Operating temperature max. [°F] | 113 °f |
| Ambient temperature min. [F] | -4 °f |
| Ambient temperature max. [F] | 158 °f |
| Ambient humidity non-condensing max [%] | 85 |
| Prop 65 label required? | Yes |

## Product information and application use

The Smatrix Pulse Communication Module (R-208) offers expanded functionality for the Smatrix Pulse wireless control system, including comfort setting, room bypass, and supply temperature monitoring, along with connectivity to the Smatrix Pulse App for remote system control.




C: HEIGHT WITH STANDARD BACK-MOUNT CASE
D: HEIGHT WITH DIN-RAIL BACK-MOUNT CASE

| Part name | Part no. | A [inch] | B [inch] | C [inch] | D [inch] | Operating voltage AC [VAC] | Weight per UOM [lbs/UOM] |
|---|---|---|---|---|---|---|---|
| Smatrix Pulse Communication Module (R-208), replacement part | A3801208 | 4.331 | 4.331 | 0.827 | 1.024 | 115 | 0.35 |

| Part name | Part no. | Codes | Standards | Listings |
|---|---|---|---|---|
| Módulo de comunicación Smatrix Pulse (R-208), piezas de reemplazo | A3801208 | - | FCC KDB996369 D04\|IC RSS-210\|ICC RSS-Gen\|FCC 47 CFR Part 15 | IC 7664A-SM4NA1\|FCC ID V9MSM4NA1 |

## Installation

Refer to the Smatrix Pulse Installation and Operation Manual for installation information.

## Related applications

Radiant

Hydronic Heating & Cooling

Tools & Accessories

## Footnotes

-

## Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517

© 2026 Uponor North America. All Rights Reserved