

Thermal Single Ecoflex

Renseignements sur le projet

|                             |                     |
|-----------------------------|---------------------|
| Nom du poste :              | Lieu :              |
| Ingénieur :                 | Date de soumission: |
| Entrepreneur :              | Présentée par:      |
| Représentant du fabricant : | Approuvé par :      |

Données techniques

|                       |                                                                                     |
|-----------------------|-------------------------------------------------------------------------------------|
| Material              | PEX                                                                                 |
| Subcomponent Material | Material Jacket: Corrugated seamless high-density polyethylene (HDPE); UV-protected |
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar)                                                   |
|                       | 180 °F (82 °C) at 100 psi (6.9 bar)                                                 |
|                       | 200 °F (93 °C) at 80 psi (5.5 bar)                                                  |

Informations sur le produit et utilisation de l'application

Uponor's Ecoflex® Thermal Single is a pre-insulated pipe for buried or aboveground commercial and residential hydronic heating and cooling applications. Service pipes are made from durable Engel-method crosslinked polyethylene (PEX-a) tubing with multilayer PEX-foam insulation and covered by a corrugated, waterproof HDPE jacket. Use with ProPEX® Fittings or WIPEX™ dezincification-resistant (DZR) brass compression fittings.1



| Nom de la pièce                                      | Numéro de pièce | R value |
|------------------------------------------------------|-----------------|---------|
| 3/4" Thermal Single with 2.7" Jacket, 1,000-ft. coil | 5012775         | 9.3     |
| 1" Thermal Single with 2.7" Jacket, 1,000-ft. coil   | 5012710         | 7.4     |
| 1" Thermal Single with 5.5" Jacket, 600-ft. coil     | 5015510         | 12.3    |
| 1 1/4" Thermal Single with 5.5" Jacket, 500-ft. coil | 5015513         | 10.7    |
| 1 1/2" Thermal Single with 6.9" Jacket, 300-ft. coil | 5016915         | 10.8    |
| 2" Thermal Single with 6.9" Jacket, 300-ft. coil     | 5016920         | 8.9     |
| 2 1/2" Thermal Single with 6.9" Jacket, 300-ft. coil | 5016925         | 7.2     |
| 3" Thermal Single with 7.9" Jacket, 300-ft. coil     | 5017930         | 7       |
| 3 1/2" Thermal Single with 7.9" Jacket, 300-ft. coil | 5017935         | -       |
| 4" Thermal Single with 7.9" Jacket, 300-ft. coil     | 5017940         | 4.8     |

| Nom de la pièce                                                                 | Numéro de pièce | Les codes                             | Normes                                                           | Annonces                      |
|---------------------------------------------------------------------------------|-----------------|---------------------------------------|------------------------------------------------------------------|-------------------------------|
| Thermal Single Ecoflex                                                          | All             | UPC IPC NPC of<br>Canada UMC NSPC IMC | ASTM F1960                                                       | cNSFus-rfh cNSFus-pw U.P.Code |
| In addition, the following parts have additional codes, standards, or listings: |                 |                                       |                                                                  |                               |
| 3/4" Thermal Single with 2.7" Jacket,<br>1,000-ft. coil                         | 5012775         |                                       | CSA B137.5 NSF/ANSI/CAN<br>61 NSF/ANSI 14                        |                               |
| 1" Thermal Single with 2.7" Jacket,<br>1,000-ft. coil                           | 5012710         |                                       | ASTM F877 NSF/ANSI/CAN 61 ASTM<br>F876 NSF/ANSI 14               |                               |
| 1" Thermal Single with 5.5" Jacket,<br>600-ft. coil                             | 5015510         |                                       | ASTM F877 NSF/ANSI/CAN 61 ASTM<br>F876 NSF/ANSI 14               |                               |
| 1 1/4" Thermal Single with 5.5" Jacket,<br>500-ft. coil                         | 5015513         |                                       | ASTM F877 NSF/ANSI/CAN 61 ASTM<br>F876 NSF/ANSI 14               |                               |
| 1 1/2" Thermal Single with 6.9" Jacket,<br>300-ft. coil                         | 5016915         |                                       | ASTM F877 NSF/ANSI/CAN 61 ASTM<br>F876 NSF/ANSI 14               |                               |
| 2" Thermal Single with 6.9" Jacket,<br>300-ft. coil                             | 5016920         |                                       | ASTM F877 NSF/ANSI/CAN 61 ASTM<br>F876 NSF/ANSI 14               |                               |
| 2 1/2" Thermal Single with 6.9" Jacket,<br>300-ft. coil                         | 5016925         |                                       | ASTM F877 CSA<br>B137.5 NSF/ANSI/CAN 61 ASTM<br>F876 NSF/ANSI 14 |                               |
| 3" Thermal Single with 7.9" Jacket,<br>300-ft. coil                             | 5017930         |                                       | ASTM F877 CSA<br>B137.5 NSF/ANSI/CAN 61 ASTM<br>F876 NSF/ANSI 14 |                               |
| 3 1/2" Thermal Single with 7.9" Jacket,<br>300-ft. coil                         | 5017935         |                                       | ASTM F877 CSA B137.5 ASTM<br>F876 NSF-61 ASTM F876 NSF-14        |                               |
| 4" Thermal Single with 7.9" Jacket,<br>300-ft. coil                             | 5017940         |                                       | ASTM F877 CSA<br>B137.5 NSF/ANSI/CAN 61 ASTM<br>F876 NSF/ANSI 14 |                               |

| L'installation                                                                                                                                                                                                                                                                                                                                                                                | Applications connexes                |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|
| Install Ecoflex Thermal Single pre-insulated pipe in buried or aboveground hydronic heating and cooling applications. Use Uponor ProPEX or WIPEX DZR brass compression fittings. Ecoflex End Caps are required on all exposed ends of Ecoflex pipes to avoid ground water contamination. For more information, refer to the Uponor Pre-insulated Pipe Systems Design and Installation Manual. | Pre-Insulated Pipe Systems           |
|                                                                                                                                                                                                                                                                                                                                                                                               | Hydronic Heating and Cooling Systems |
|                                                                                                                                                                                                                                                                                                                                                                                               | Radiant Heating and Cooling Systems  |
|                                                                                                                                                                                                                                                                                                                                                                                               | Permafrost Prevention Systems        |
|                                                                                                                                                                                                                                                                                                                                                                                               | Turf Conditioning Systems            |

| Notes de bas de page | Coordonnées de la personne-ressource                                                                |                                                                                                 |
|----------------------|-----------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|
| -                    | Uponor Inc.<br>5925 148th Street West<br>Apple Valley, MN 55124<br>T 800.321.4739<br>F 952.891.2008 | Uponor Ltd.<br>6510 Kennedy Road<br>Mississauga, ON L5T 2X4<br>T 888.594.7726<br>F 800.638.9517 |