

# Accessoires Ecoflex en PEX plus pour eau potable

## Renseignements sur le projet

Nom du poste :	Lieu :
Ingénieur :	Date de soumission:
Entrepreneur :	Présentée par:
Représentant du fabricant :	Approuvé par :

## Données techniques

Material Body: polyamide; conductors: nickel-coated brass

## Informations sur le produit et utilisation de l'application

Uponor heat-trace end seal is part of a universal power termination and splicing system for Uponor Ecoflex® potable PEX plus pre-insulated piping systems.



Nom de la pièce	Numéro de pièce	Weight per UOM [lbs/UOM]
Heat-trace Power Terminal Block	5992000	1.27
Heat-trace End Seal, SF-E	5993000	0.05
Heat-trace Tee Splice, SF-T	5994000	1.18

## L'installation

Simply cut back one wire 1/4" (6mm) and push it into the end seal. For additional information, refer to the Uponor Ecoflex Pre-insulated Pipe Systems Design and Installation Manual.

## Applications connexes

- Pre-Insulated Pipe Systems
- Permafrost Prevention Systems
- PEX-a Plumbing Systems

Les codes	Normes	Annonces
-	-	IECEX SIR 11.0136U

## Remarques :

Power cable:  
3c x 2.5mm<sup>2</sup> (supplied by others)  
Power cable entry: Gland provided as standard; insert appropriate supplied bush into the gland

## Notes de bas de page

## Coordonnées de la personne-ressource

-	Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008	Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517
---	---	---