

Accessoires Ecoflex en PEX plus pour eau potable

Renseignements sur le projet

Nom du poste :	Lieu :
Ingénieur :	Date de soumission:
Entrepreneur :	Présentée par:
Représentant du fabricant :	Approuvé par :

Données techniques

Ambient temperature min. [F] -40 °f
Ambient temperature max. [F] 122 °f

Informations sur le produit et utilisation de l'application

Uponor heat-trace end seal is part of a universal power termination and splicing system for Uponor Ecoflex® potable PEX plus pre-insulated piping systems.



Nom de la pièce	Numéro de pièce	Material group	Operating voltage [V]	Output rating at 24VAC [A]	Subcomponent Material	Weight per UOM [lbs/UOM]
Heat-trace Power Terminal Block	5992000	Body: polyamide; conductors: nickel-coated brass	275	16	-	1.27
Heat-trace End Seal, SF-E	5993000	-	275	16	Body: polyamide; conductors: nickel-coated brass	0.05
Heat-trace Tee Splice, SF-T	5994000	-	275	16	Body: polyamide; conductors: nickel-coated brass	1.18

Nom de la pièce	Numéro de pièce	Les codes	Normes	Annonces
Accessoires Ecoflex en PEX plus pour eau potable	All	-	-	IECEX SIR 11.0136U

L'installation	Applications connexes
Simply cut back one wire ¼" (6mm) and push it into the end seal. For additional information, refer to the Uponor Ecoflex Pre-insulated Pipe Systems Design and Installation Manual.	Pre-Insulated Pipe Systems Permafrost Prevention Systems PEX-a Plumbing Systems

Remarques :
Power cable: 3c x 2.5mm2 (supplied by others) Power cable entry: Gland provided as standard; insert appropriate supplied bush into the gland

Notes de bas de page	Coordonnées de la personne-ressource
-	Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008 Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517