

# Adaptateurs et raccords droits filetés pour collecteur en laiton



## Renseignements sur le projet


Nom du poste :	Lieu :
Ingénieur :	Date de soumission:
Entrepreneur :	Présentée par:
Représentant du fabricant :	Approuvé par :

## Données techniques

End type 1	ISO 228-G 1-1/4"
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)
Prop 65 label required?	Yes

## Informations sur le produit et utilisation de l'application

Uponor's Threaded Brass Manifold Bushings are used in TruFLOW™ manifolds. In radiant heating applications, the bushing transitions the R32 manifold union nut to 1" national pipe thread (NPT) and 3/4" threaded connections (PEX or Multi-layer Composite (MLC) tubing with QS-style fittings).



Nom de la pièce	Numéro de pièce	A [inch]	B [inch]	C [inch]	D [inch]	E [inch]	F [inch]	G [inch]	H [inch]	Weight per UOM [lbs/UOM]	Material group
Threaded Brass Manifold Bushing, R32 Male x 1" Female NPT	A2123210	1.918	1.687	0.985	1	-	-	-	-	0.3	-
Threaded Brass Manifold Bushing, R32 Male x 3/4" Female NPT	A2133275	2.018	1.75	0.985	-	-	-	-	-	0.44	-
Threaded Brass Manifold Straight Adapter, R32 Male x R20 Male	A4143220	0.635	0.35	0.599	2.02	1.584	1.75	1.01	0.875	0.55	-
Threaded Brass Manifold Straight Adapter, R32 Male x R25 Male	A4143225	0.613	0.35	0.635	2.02	1.598	1.75	1.01	0.875	0.5	-

Nom de la pièce	Numéro de pièce	End Type 2
Threaded Brass Manifold Bushing, R32 Male x 1" Female NPT	A2123210	FNPT 1"
Threaded Brass Manifold Bushing, R32 Male x 3/4" Female NPT	A2133275	FNPT 3/4"
Threaded Brass Manifold Straight Adapter, R32 Male x R20 Male	A4143220	ISO 228-G 3/4"
Threaded Brass Manifold Straight Adapter, R32 Male x R25 Male	A4143225	ISO 228-G 1"

## L'installation

Thread directly into Uponor TruFLOW manifolds. For additional information, refer to the TruFLOW Manifold Instruction Sheet or the Uponor Radiant Floor Heating Installation Handbook.

## Applications connexes

- Radiant Heating and Cooling Systems
- Permafrost Protection Systems
- Turf Conditioning Systems

Les codes	Normes	Annonces
IMC IRC NBC of Canada UMC	CSA B137.5 R32:	cNSFus-rfh

## Notes de bas de page

## Coordonnées de la personne-ressource

-	Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008	Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517
---	---	---