

# Raccordements soudés pour collecteur TruFLOW Classic

## Renseignements sur le projet

Nom du poste :	Lieu :
Ingénieur :	Date de soumission:
Entrepreneur :	Présentée par:
Représentant du fabricant :	Approuvé par :

## Données techniques

Material	Brass
End type 1	ISO 228-G 1-1/4"
End type 2	ISO 228-G 1-1/4"
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)
Prop 65 label required?	Yes



## Informations sur le produit et utilisation de l'application

The TruFLOW™ Modular Manifold Elbow Union features a R32 union on one side with 1/4" male BSP thread on the other side. Use

Nom de la pièce	Numéro de pièce	A [mm]	B [mm]	C [mm]	Weight per UOM [kg/UOM]
TruFLOW Classic Manifold Elbow Union, R32 Union x 1/4" BSP	A2620090	64.95	63.45	46	0.308

Nom de la pièce	Numéro de pièce	Les codes	Normes	Annonces
Raccordements soudés pour collecteur TruFLOW Classic	A2620090	-	R32: ISO 228-G 1/4"   ASTM F877	-

## L'installation

Use the TruFLOW Modular Manifold Elbow Union to make the connection between TruFLOW Manifolds and R32 Manifold Adapters. Remove the existing straight union assembly from the manifold in order to install the Elbow Union. Use Uponor Silicone Oil on the male threads to ease installation. Use only with TruFLOW Manifolds. Accessories include Replacement O-ring for 1/4" BSP Connections (A2620008) and Replacement Gasket for R32 Union Connections (A2620005). Refer to the Uponor Radiant Installation Handbook for additional information.

## Applications connexes

- Radiant Heating and Cooling Systems
- Turf Conditioning Systems
- Permafrost Protection Systems

## Remarques :

Connection:  
1/4" male BSP x R32

## Notes de bas de page

## Coordonnées de la personne-ressource

-	<p>Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008</p>	<p>Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517</p>
---	--	--