

# Embout de raccordement pour collecteur TruFLOW

## Renseignements sur le projet

|                             |                     |
|-----------------------------|---------------------|
| Nom du poste :              | Lieu :              |
| Ingénieur :                 | Date de soumission: |
| Entrepreneur :              | Présentée par:      |
| Représentant du fabricant : | Approuvé par :      |

## Données techniques

|                         |                                                                                                                |
|-------------------------|----------------------------------------------------------------------------------------------------------------|
| Material                | Brass                                                                                                          |
| Manifold size           | 1.25 inch                                                                                                      |
| End type 1              | ISO 228-G 1-1/4"                                                                                               |
| End type 2              | ISO 228-G 1-1/4"                                                                                               |
| Temp/pressure ratings   | 73 °F (23 °C) at 160 psi (11 bar)<br>180 °F (82 °C) at 100 psi (6.9 bar)<br>200 °F (93 °C) at 80 psi (5.5 bar) |
| Max. fluid flow rate    | 21 gpm                                                                                                         |
| Prop 65 label required? | Yes                                                                                                            |

## Informations sur le produit et utilisation de l'application

The Uponor TruFLOW™ Classic Manifold Extension Kit is designed for easy, inline extension of up to two additional loops for the TruFLOW Classic Manifold Assembly. The kit contains two 1½" BSP nipples, one supply manifold, one return manifold and two loop end caps. Use silicone oil lubricant on the male threads to ease installation.



| Nom de la pièce                                           | Numéro de pièce | Weight per UOM [kg/UOM] |
|-----------------------------------------------------------|-----------------|-------------------------|
| TruFLOW Manifold Coupling Nipple, 1 1/4" BSP x 1 1/4" BSP | A2621010        | 0.136                   |

| Nom de la pièce                                | Numéro de pièce | Les codes | Normes                                             | Annonces |
|------------------------------------------------|-----------------|-----------|----------------------------------------------------|----------|
| Embout de raccordement pour collecteur TruFLOW | A2621010        | -         | R32: ISO 228-G 1½"   ASTM F877   R20: ISO 228-G ¾" | -        |

| L'installation                                                                                                                                                                                                                                                                                                                                                                                                                   | Applications connexes                                                                             |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------|
| Use the supplied TruFLOW Classic Manifold Coupling Nipple to attach the TruFLOW Manifold Extension Kit to the desired TruFLOW Manifold. Use the TruFLOW Balancing Hex Key (A2620002) on the internal balancing valves of the supply manifold. Manifold is shipped with the appropriate number of TruFLOW Manifold Actuator Adapters (A2630028). Refer to the TruFLOW Classic Manifold Instruction Sheet for further information. | Radiant Heating and Cooling Systems<br>Permafrost Prevention Systems<br>Turf Conditioning Systems |

| Remarques :                                               |
|-----------------------------------------------------------|
| Manifold loop threaded connections:<br>ISO 228-G ¾" (R20) |

| Notes de bas de page | Coordonnées de la personne-ressource                                                                                                                                                                                                                |
|----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| -                    | <div> <p>Uponor Inc.<br/>5925 148th Street West<br/>Apple Valley, MN 55124<br/>T 800.321.4739<br/>F 952.891.2008</p> </div> <div> <p>Uponor Ltd.<br/>6510 Kennedy Road<br/>Mississauga, ON L5T 2X4<br/>T 888.594.7726<br/>F 800.638.9517</p> </div> |