

Adaptateurs pour raccord en cuivre de type QS

Renseignements sur le projet


Nom du poste :	Lieu :
Ingénieur :	Date de soumission:
Entrepreneur :	Présentée par:
Représentant du fabricant :	Approuvé par :

Données techniques

Material	Brass
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)
Prop 65 label required?	Yes

Informations sur le produit et utilisation de l'application

The Uponor QS-style Copper Adapters, combined with the appropriate QS-style Fitting Assembly, transition Wirsbo hePEX™ tubing to 1/2", 3/4" or 1" copper pipe in hydronic heating applications



Nom de la pièce	Numéro de pièce	A [inch]	B [inch]	C [inch]	D [inch]	E [inch]	F [inch]	G [inch]	H [inch]	Weight per UOM [lbs/UOM]	End Type 1
QS-style Copper Fitting Adapter, R20 x 1/2" Copper	A4342050	0.601	0.275	0.512	1.224	1.388	1.063	0.612	0.531	0.15	ISO 228-G 3/4"
QS-style Copper Fitting Adapter, R20 x 3/4" Copper	A4342075	0.85	0.275	0.512	1.224	1.637	1.063	0.612	0.531	0.18	ISO 228-G 3/4"
QS-style Copper Fitting Adapter, R25 X 1" Copper (for 3/4" and 5/8" tubing only)	A4342510	0.97	0.299	0.658	1.585	1.927	1.375	0.792	0.687	0.29	ISO 228-G 1"
QS-style Copper Fitting Adapter, R25 X 3/4" Copper (for 3/4" and 5/8" tubing only)	A4342575	0.935	0.3	0.657	1.557	1.892	1.375	0.778	0.687	0.28	ISO 228-G 1"

Nom de la pièce	Numéro de pièce	End Type 2
QS-style Copper Fitting Adapter, R20 x 1/2" Copper	A4342050	Sweat 1/2"
QS-style Copper Fitting Adapter, R20 x 3/4" Copper	A4342075	Sweat 3/4"
QS-style Copper Fitting Adapter, R25 X 1" Copper (for 3/4" and 5/8" tubing only)	A4342510	Sweat 1"
QS-style Copper Fitting Adapter, R25 X 3/4" Copper (for 3/4" and 5/8" tubing only)	A4342575	Sweat 3/4"

L'installation

The corresponding compression fitting threads onto the R20 or R25 thread to adapt to copper. For additional information, refer to the Uponor Radiant Floor Heating Installation Handbook.

Applications connexes

- Radiant Heating and Cooling Systems
- Permafrost Protection Systems
- Turf Conditioning Systems

Les codes

Normes

Annonces

- ASTM F877|R20: -

Notes de bas de page

Coordonnées de la personne-ressource

-	<p>Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008</p>	<p>Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517</p>
---	--	--