Rouleaux blancs Uponor AquaPEX

Renseignements sur le projet

Nom du poste :	Lieu :
Ingénieur :	Date de soumission:
Entrepreneur :	Présentée par:
Représentant du fabricant :	Approuvé par :

Données techniques

Material	PEX
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)



Informations sur le produit et utilisation de l'application

Uponor AquaPEX White is an Engel-method, PEX-a pipe designed for hot and cold domestic potable water distribution and residential fire safety as well as radiant heating/cooling and hydronic piping systems containing no ferrous corrodible components or where ferrous components are isolated from the piping. The product features a black print string that displays the brand name, manufacturing method, and various codes, standards, and listings.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.

	Nom de la pièce	Numéro de pièce	Inner diameter coil [inch]	Outer diameter coil [inch]	Coil width [inch]	Inner diameter pipe [inch]	Outer diameter pipe [inch]	Weight per UOM [lbs/UOM]
	1/4" Uponor AquaPEX White, 100-ft. coil	F1040250	10.5	16	2.5	0.241	0.375	4
	3/8" Uponor AquaPEX White, 400-ft. coil	F1090375	15.75	32	4.5	0.35	0.5	20
	3/8" Uponor AquaPEX White, 1,000-ft. coil	F1120375	15.75	32	6.5	0.35	0.5	44
	1/2" Uponor AquaPEX White, 100-ft. coil	F1040500	15.75	23.5	3.5	0.475	0.625	6
	1/2" Uponor AquaPEX White, 300-ft. coil	F1060500	19.7	32	4	0.475	0.625	18
	1/2" Uponor AquaPEX White, 500-ft. coil	F1100500	15.75	32	6.5	0.475	0.625	27.6
	1/2" Uponor AquaPEX White, 1,000-ft. coil	F1120500	15.75	32	10.5	0.475	0.625	54
	5/8" Uponor AquaPEX White, 300-ft. coil	F1060625	15.75	32	6.5	0.574	0.75	28
	5/8" Uponor AquaPEX White, 1,000-ft. coil	F1120625	15.75	32	16	0.574	0.75	86
	3/4" Uponor AquaPEX White, 100-ft. coil	F1040750	15.75	32	3	0.671	0.875	10
	3/4" Uponor AquaPEX White, 300-ft. coil	F1060750	22	32	8	0.671	0.875	34
	3/4" Uponor AquaPEX White, 500-ft. coil	F1100750	15.75	32	10.5	0.671	0.875	54
	1" Uponor AquaPEX White, 100-ft. coil	F1041000	22.7	32	6.5	0.862	1.125	20
	1" Uponor AquaPEX White, 300-ft. coil	F1061000	22.7	32	16	0.862	1.125	56
	1" Uponor AquaPEX White, 500-ft. coil	F1101000	22.7	40	13.8	0.862	1.125	93
	1 1/4" Uponor AquaPEX White, 100-ft. coil	F1061250	27	45	6	1.054	1.375	34
	1 1/4" Uponor AquaPEX White, 300-ft. coil	F1021250	27	45	18.5	1.054	1.375	106
	1 1/2" Uponor AquaPEX White, 100-ft. coil	F1061500	27	45	6	1.244	1.625	44
	1 1/2" Uponor AquaPEX White, 300-ft. coil	F1021500	27	45	19	1.244	1.625	133
	2" Uponor AquaPEX White, 100-ft. coil	F1062000	26.5	44	9	1.629	2.125	68.2
	2" Uponor AquaPEX White, 200-ft. coil	F1052000	27	46	13	1.629	2.125	136.4
	2" Uponor AquaPEX White, 300-ft. coil	F1022000	26.5	51	15	1.629	2.125	204.6
✔	2 1/2" Uponor AquaPEX White, 100-ft. coil	F1062500	64	80	16	2.011	2.625	88
	3" Uponor AquaPEX White, 100-ft. coil	F1063000	62.5	80	19	2.398	3.125	128

© 2026 Uponor Amérique du Nord. Tous droits réservés

Nom de la pièce	Numéro de pièce	Les codes	Normes	Annonces
Rouleaux blancs Uponor AquaPEX	All	UPC|IMC|NBC of Canada|IPC|IBC|IRC|UMC|NSPC|UFGS|NPC of Canada	ASTM E119/UL 263|ASTM F1960|ASTM E84|ASTM F2023|ASTM E814/ULC S115|CSA B214|CSA B137.5|NSF/ANSI 14|NSF/ANSI/CAN 61|ASTM F876|ASTM F877|ULC S102.2|ULC S101	IAPMO-ES|ICC-ES-PMG|CSA|CCMC|PPI TR-4|cQAIus P321|UL|U.P.Code|HUD MR 1269|BMEC
In addition, the following parts have additional codes, standards, or listings:				
1/4" Uponor AquaPEX White, 100-ft. coil	F1040250			cNSFus-pw
3/8" Uponor AquaPEX White, 400-ft. coil	F1090375			cNSFus-pw
3/8" Uponor AquaPEX White, 1,000-ft. coil	F1120375			cNSFus-pw
1/2" Uponor AquaPEX White, 100-ft. coil	F1040500			cNSFus-pw
1/2" Uponor AquaPEX White, 300-ft. coil	F1060500			cNSFus-pw
1/2" Uponor AquaPEX White, 500-ft. coil	F1100500			cNSFus-pw
1/2" Uponor AquaPEX White, 1,000-ft. coil	F1120500			cNSFus-pw
5/8" Uponor AquaPEX White, 300-ft. coil	F1060625			cNSFus-pw
5/8" Uponor AquaPEX White, 1,000-ft. coil	F1120625			cNSFus-pw
3/4" Uponor AquaPEX White, 100-ft. coil	F1040750		UL 1821	cNSFus-pw-fs
3/4" Uponor AquaPEX White, 300-ft. coil	F1060750		UL 1821	cNSFus-pw-fs
3/4" Uponor AquaPEX White, 500-ft. coil	F1100750		UL 1821	cNSFus-pw-fs
1" Uponor AquaPEX White, 100-ft. coil	F1041000		UL 1821	cNSFus-pw-fs
1" Uponor AquaPEX White, 300-ft. coil	F1061000		UL 1821	cNSFus-pw-fs
1" Uponor AquaPEX White, 500-ft. coil	F1101000		UL 1821	cNSFus-pw-fs
1 1/4" Uponor AquaPEX White, 100-ft. coil	F1061250		UL 1821	cNSFus-pw-fs
1 1/4" Uponor AquaPEX White, 300-ft. coil	F1021250		UL 1821	cNSFus-pw-fs
1 1/2" Uponor AquaPEX White, 100-ft. coil	F1061500			cNSFus-pw
1 1/2" Uponor AquaPEX White, 300-ft. coil	F1021500			cNSFus-pw
2" Uponor AquaPEX White, 100-ft. coil	F1062000			cNSFus-pw
2" Uponor AquaPEX White, 200-ft. coil	F1052000			cNSFus-pw
2" Uponor AquaPEX White, 300-ft. coil	F1022000			cNSFus-pw
2 1/2" Uponor AquaPEX White, 100-ft. coil	F1062500			cNSFus-pw
3" Uponor AquaPEX White, 100-ft. coil	F1063000			cNSFus-pw

L'installation	Applications connexes
Use ProPEX® fittings for $^{3}/_{8}$" through 3" pipe. 1 Refer to the ProPEX Connections Instructional Guide, Uponor Piping Pocket Guide, Plumbing Design Assistance Manual (PDAM), Complete Design Assistance Manual (CDAM), Hydronic Piping Design Assistance Manual (HPDAM) or AquaSAFE™ Residential Fire Sprinkler Installation Guide for more information.	PEX-a Plumbing Systems Radiant Heating and Cooling Systems Hydronic Piping Systems

© 2026 Uponor Amérique du Nord. Tous droits réservés

Notes de bas de page	Coordonnées de la personne-ressource	
	Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008	Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517
-		

© 2026 Uponor Amérique du Nord. Tous droits réservés