

Rouleaux pré-manchonnés Uponor AquaPEX

Renseignements sur le projet

Nom du poste :	Lieu :
Ingénieur :	Date de soumission:
Entrepreneur :	Présentée par:
Représentant du fabricant :	Approuvé par :

Données techniques

Material	PEX
Subcomponent Material	Sleeve:
	High-density polyethylene (HDPE)
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar)
	180 °F (82 °C) at 100 psi (6.9 bar)
	200 °F (93 °C) at 80 psi (5.5 bar)

Informations sur le produit et utilisation de l'application

Pre-sleeved Uponor AquaPEX® tubing is used in hot and cold water-distribution systems. The highdensity polyethylene (HDPE) corrugated sleeve provides protection for installations in concrete slabs or soil, and allows for removal and replacement of the tubing if required. Note: This tubing can also be used in radiant heating and cooling systems containing no ferrous corrodible components or where ferrous components are isolated from the tubing.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.



Nom de la pièce	Numéro de pièce	Les codes	Normes	Annonces
Rouleaux pré-manchonnés Uponor AquaPEX	All	IMC UPC IBC IRC NBC of Canada IPC UFGS NPC of Canada UMC NSPC	ASTM F1960 ASTM E119/UL 263 ASTM F876 ASTM F2023 ASTM E814/ULC S115 ASTM F877 CSA B137.5 CSA B214 ULC S101	IAPMO-ES ICC-ES-PMG CCMC PPI TR-4 CSA UL U.P.Code cQAIus P321 HUD MR 1269 BMEC

L'installation	Applications connexes
Approved fitting system is ProPEX®. 1 The installer can tie tubing to rebar with standard steel wire or other fastening devices. Pre-sleeved Uponor AquaPEX tubing will fit in all Uponor concrete floor tube brackets. Refer to the ProPEX Connections Instructional Guide, Uponor Piping Pocket Guide or Plumbing Design Assistance Manual (PDAM) for more information.	PEX-a Plumbing Systems Radiant Heating and Cooling Systems

Remarques :

Application temperature continuous operation of sleeve:
5°F (-15°C) to 194°F (90°C)

Application temperature continuous operation of sleeve:
5°F (-15°C) to 194°F (90°C)

Notes de bas de page	Coordonnées de la personne-ressource
-	Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008 Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517