

Longueurs droites blanches Uponor AquaPEX

Renseignements sur le projet

| | |
|-----------------------------|---------------------|
| Nom du poste : | Lieu : |
| Ingénieur : | Date de soumission: |
| Entrepreneur : | Présentée par: |
| Représentant du fabricant : | Approuvé par : |

Données techniques

| | |
|-----------------------|--|
| Material | PEX |
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar) |

Informations sur le produit et utilisation de l'application

Uponor AquaPEX White, straight length pipe, is used for hot and cold domestic potable water distribution, residential fire safety and radiant heating and cooling and hydronic piping systems containing no ferrous corrodible components or where ferrous components are isolated from the piping.



| Nom de la pièce | Numéro de pièce | Inner diameter coil [inch] | Outer diameter coil [inch] | Coil width [inch] | Inner diameter pipe [inch] | Outer diameter pipe [inch] | Weight per UOM [lbs/UOM] |
|---|-----------------|----------------------------|----------------------------|-------------------|----------------------------|----------------------------|--------------------------|
| 1" Uponor AquaPEX White, 20-ft. straight length, 200 ft. (10 per bundle) | F1921000 | 4 | 258 | 4 | 0.862 | 1.125 | 38 |
| 1 1/4" Uponor AquaPEX White, 20-ft. straight length, 100 ft. (5 per bundle) | F1921250 | 4.5 | 258 | 4.5 | 1.054 | 1.375 | 25 |
| 1 1/2" Uponor AquaPEX White, 20-ft. straight length, 100 ft. (5 per bundle) | F1921500 | 5 | 258 | 5 | 1.244 | 1.625 | 35 |
| 2" Uponor AquaPEX White, 20-ft. straight length, 100 ft. (5 per bundle) | F1922000 | 10.75 | 264 | 10.8 | 1.629 | 2.125 | 60.5 |
| 2 1/2" Uponor AquaPEX White, 20-ft. straight length, 60 ft. (3 per bundle) | F1922500 | 10.75 | 264 | 10.8 | 2.011 | 2.625 | 55.2 |
| 3" Uponor AquaPEX White, 20-ft. straight length, 40 ft. (2 per bundle) | F1923000 | 10.75 | 264 | 10.8 | 2.398 | 3.125 | 53.1 |
| 1/2" Uponor AquaPEX White, 20-ft. straight length, 500 ft. (25 per bundle) | F1930500 | 3.5 | 258 | 3.5 | 0.475 | 0.625 | 28 |
| 3/4" Uponor AquaPEX White, 20-ft. straight length, 300 ft. (15 per bundle) | F1930750 | 4.5 | 258 | 4.5 | 0.671 | 0.875 | 31 |

L'installation

Use ProPEX® fittings for 3/8" through 3" pipe.1 Refer to the ProPEX Connections Instructional Guide, Uponor Piping Pocket Guide, Plumbing Design Assistance Manual (PDAM), Complete Design Assistance Manual (CDAM), Hydronic Piping Design Assistance Manual (HPDAM) or AquaSAFE™ Residential Fire Sprinkler Installation Guide for more information

Applications connexes

PEX-a Plumbing Systems
Radiant Heating and Cooling Systems
Hydronic Piping Systems

Les codes

IMC|UPC|IBC|IRC|NBC of Canada|IPC|IFGS|NPC of Canada|UMC|NSPC

Normes

ASTM F1960|ASTM E119|UL 263|ASTM F876|ASTM E84|ASTM F2023|ASTM E814|ULC S115|ASTM F877|CSA B137.5|ULC S102.2|CSA B214|NSF-61|ULC S101|NSF-14*

Annonces

IAPMO-ES|ICC-ES-PMG|cNSFus-pw|CCMC|PPI TR-4|CSA|UL|U.P.Code|cQAlus P321|HUD MR 1269|BMEC*

Notes de bas de page

* Certaines SKU de cette famille ont des codes, des normes ou des listes supplémentaires. Veuillez consulter uponor.com pour obtenir des renseignements complets.

Coordonnées de la personne-ressource

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517