Attaches pour PEX

Renseignements sur le projet

Nom du poste :	Lieu :
Ingénieur :	Date de soumission:
Entrepreneur :	Présentée par:
Représentant du fabricant :	Approuvé par :

Données techniques

Material	Plastic
Subcomponent Material	Nylon

Informations sur le produit et utilisation de l'application

Uponor PEX Clips are designed to suspend crosslinked polyethylene (PEX) tubing below the underside of a subfloor in a joist cavity installation.



	Nom de la pièce	Numéro de pièce	A [inch]	B [inch]	C [inch]	Prop 65 label required?	Weight per UOM [lbs/UOM]
	3/8" PEX Clip, 100/pkg.	F7060375	0.685	1.14	1.613	-	0.015
	1/2" PEX Clip, 100/pkg.	F7051258	0.685	1.14	1.676	-	0.016
	3/4" PEX Clip, 100/pkg.	F7057500	0.685	1.386	1.912	No	-
✔	1" PEX Clip, 50/pkg.	F7051001	0.685	1.77	2.202	No	0.03

L'installation

Mount the PEX Clips to the underside of the subfloor in the joist cavity with the use of a drywall screw or nail. Secure the tubing to the clips at 36" intervals along the joist cavity. Refer to the Uponor Radiant Installation Handbook for additional information.

Applications connexes

Radiant Heating and Cooling Systems

Notes de bas de page

-

Coordonnées de la personne-ressource

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517

© 2026 Uponor Amérique du Nord. Tous droits réservés