

# Coudes au quart droits ProPEX en cuivre sans plomb (LF)

## Renseignements sur le projet

Nom du poste :	Lieu :
Ingénieur :	Date de soumission:
Entrepreneur :	Présentée par:
Représentant du fabricant :	Approuvé par :

## Données techniques

Material	Copper
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)
Prop 65 label required?	Yes

## Informations sur le produit et utilisation de l'application

ProPEX® Lead-free (LF) Copper Straight Stub transitions Uponor PEX tubing to copper pipe for use in hot and cold domestic potable water systems and hydronic radiant heating and cooling systems. 1 The transition fitting can be used for direct transition to copper sweat, copper press and roll-groove applications. The transition fitting is safe for direct burial in soil.



Nom de la pièce	Numéro de pièce	A [inch]	B [inch]	C [inch]	D [inch]	Weight per UOM [lbs/UOM]	End Type 1	End Type 2
ProPEX LF Copper Straight Stub, 1/2" PEX LF Brass x 1/2" Copper (8")	LF2935050	8.3	0.709	7.592	0.77	0.22	ProPEX 1/2"	Copper 1/2"
ProPEX LF Copper Straight Stub, 1/2" PEX LF Brass x 1/2" Copper (15")	LF2945050	14.5	0.709	13.792	0.77	0.4	ProPEX 1/2"	Copper 1/2"
ProPEX LF Copper Straight Stub, 2 1/2" PEX LF Brass x 2 1/2" Copper	LF2962525	12.11	2.83	9.28	3.36	3.7	ProPEX 2-1/2"	Sweat 2-1/2"
ProPEX LF Copper Straight Stub, 3" PEX LF Brass x 3" Copper	LF2963030	13.67	3.38	10.29	3.79	5.5	ProPEX 3"	Sweat 3"

## L'installation

Use the appropriate Uponor ProPEX Ring for the tubing (sold separately). Do not solder within 18 inches of the ProPEX fitting. Refer to the Uponor AquaPEX® Professional Plumbing Installation Guide or Uponor Hydronic Piping Design Assistance Manual for additional information.

## Applications connexes

- PEX-a Plumbing Systems
- Hydronic Radiant Heating and Cooling Systems
- Snow Melting Systems
- Turf Conditioning Systems
- Permafrost Prevention Systems

Les codes	Normes	Annonces
UPC IBC IRC IPC NPC of Canada UMC NSPC IMC	NSF-372 ASTM F877 ASTM F1960 CSA B137.5 NSF-61 NSF-14	IAPMO-ES CC-ES-PMG cNSFus-pw-G U.P.Code*

## Notes de bas de page

\* Certaines SKU de cette famille ont des codes, des normes ou des listes supplémentaires. Veuillez consulter uponor.com pour obtenir des renseignements complets.

## Coordonnées de la personne-ressource

Uponor Inc.  
5925 148th Street West  
Apple Valley, MN 55124  
T 800.321.4739  
F 952.891.2008

Uponor Ltd.  
6510 Kennedy Road  
Mississauga, ON L5T 2X4  
T 888.594.7726  
F 800.638.9517