# Adaptateurs ProPEX pour coude applique en laiton sans plomb (LF)

## Renseignements sur le projet

| | |
|---|---|
| Nom du poste : | Lieu : |
| Ingénieur : | Date de soumission: |
| Entrepreneur : | Présentée par: |
| Représentant du fabricant : | Approuvé par : |

## Données techniques

| | |
|---|---|
| Material | LF Brass |
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar)<br>180 °F (82 °C) at 100 psi (6.9 bar)<br>200 °F (93 °C) at 80 psi (5.5 bar) |
| Prop 65 label required? | Yes |



## Informations sur le produit et utilisation de l'application

Uponor offers the ProPEX® Lead-free Drop Ear Brass Elbow for use in hot and cold domestic potable water systems.1 One end of the adapter connects to female iron pipe (FIP) and the other end includes an Uponor ProPEX fitting for connections to Uponor AquaPEX® tubing.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.

| | Nom de la pièce | Numéro de pièce | End Type 1 | End Type 2 |
|---|---|---|---|---|
| | ProPEX LF Brass Drop Ear Elbow, 1/2" PEX x 3/8" FIP | LF4235038 | ProPEX 1/2" | FNPT 3/8" |
| ✔ | ProPEX LF Brass Drop Ear Elbow, 1/2" PEX x 1/2" FIP | LF4235050 | ProPEX 1/2" | FNPT 1/2" |
| | ProPEX LF Brass Drop Ear Elbow, 3/4" PEX x 3/4" FIP | LF4237575 | ProPEX 3/4" | FNPT 3/4" |
| | ProPEX LF Brass Drop Ear Elbow, 1" PEX x 1" FIP | LF4231010 | ProPEX 1" | FNPT 1" |

| Nom de la pièce | Numéro de pièce | Les codes | Normes | Annonces |
|---|---|---|---|---|
| Adaptateurs ProPEX pour coude applique en laiton sans plomb (LF) | All | UPC\|IBC\|IRC\|IPC\|NPC of Canada\|UMC\|NSPC\|IMC | NSF-372\|ASTM F877\|ASTM F1960\|CSA B137.5\|NSF-61\|NSF-14 | ICC-ES-PMG\|cNSFus-pw-G\|U.P.Code |

## L'installation

A ProPEX Ring is required for making ProPEX connections. Use the appropriate ProPEX Ring for tubing. For more information, refer to the Uponor Professional Plumbing Installation Guide.

## Applications connexes

PEX-a Plumbing Systems

## Notes de bas de page

-

## Coordonnées de la personne-ressource


Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517


© 2024 Uponor Amérique du Nord. Tous droits réservés