
Adaptateurs soudés à l'étain ProPEX en laiton sans plomb (LF)

Renseignements sur le projet

Nom du poste :	Lieu :
Ingénieur :	Date de soumission:
Entrepreneur :	Présentée par:
Représentant du fabricant :	Approuvé par :

Données techniques

Material	LF Brass
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)
Prop 65 label required?	Yes



Informations sur le produit et utilisation de l'application

ProPEX® lead-free (LF) brass sweat adapters transition Uponor PEX tubing to copper pipe for use in hot and cold domestic potable water systems, residential fire safety and hydronic radiant heating and cooling systems. 1 These adapters are safe for direct burial in soil.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.

	Nom de la pièce	Numéro de pièce	Cv	End Type 1	End Type 2
	ProPEX LF Brass Sweat Adapter, 3/8" PEX x 1/2" Copper	LF4513850	5.7	ProPEX 3/8"	Sweat 1/2"
	ProPEX LF Brass Sweat Adapter, 3/4" PEX x 3/4" Copper	LF4517575	13.4	ProPEX 3/4"	Sweat 3/4"
	ProPEX LF Brass Sweat Adapter, 1" PEX x 1" Copper	LF4511010	22.1	ProPEX 1"	Sweat 1"
	ProPEX LF Brass Sweat Adapter, 1 1/4" PEX x 1 1/4" Copper	LF4511313	34	ProPEX 1-1/4"	Sweat 1-1/4"
	ProPEX LF Brass Sweat Adapter, 1/2" PEX x 3/4" Copper	LF4515075	5.1	ProPEX 1/2"	Sweat 3/4"
	ProPEX LF Brass Sweat Adapter, 1/2" PEX x 1/2" Copper	LF4515050	5.7	ProPEX 1/2"	Sweat 1/2"
	ProPEX LF Brass Sweat Adapter, 3/4" PEX x 1/2" Copper	LF4517550	8.8	ProPEX 3/4"	Sweat 1/2"
	ProPEX LF Brass Sweat Adapter, 3/4" PEX x 1" Copper	LF4517510	10.9	ProPEX 3/4"	Sweat 1"
	ProPEX LF Brass Sweat Adapter, 1 1/2" PEX x 1 1/2" Copper	LF4511515	45.5	ProPEX 1-1/2"	Sweat 1-1/2"
	ProPEX LF Brass Sweat Adapter, 2" PEX x 2" Copper	LF4512020	83.6	ProPEX 2"	Sweat 2"
✔	ProPEX LF Brass Sweat Adapter, 2 1/2" PEX x 2 1/2" Copper	LF4512525	136.2	ProPEX 2-1/2"	Sweat 2-1/2"
	ProPEX LF Brass Sweat Adapter, 3" PEX x 3" Copper	LF4513030	189.1	ProPEX 3"	Sweat 3"

© 2024 Uponor Amérique du Nord. Tous droits réservés

Nom de la pièce	Numéro de pièce	Les codes	Normes	Annonces
Adaptateurs soudés à l'étain ProPEX en laiton sans plomb (LF)	All	UPC|IBC|IRC|IPC|NPC of Canada|UMC|NSPC|IMC	NSF-372|ASTM F877|ASTM F1960|CSA B137.5|NSF-61|NSF-14	IAPMO-ES|ICC-ES-PMG|U.P.Code
In addition, the following parts have additional codes, standards, or listings:				
ProPEX LF Brass Sweat Adapter, 3/8" PEX x 1/2" Copper	LF4513850			cNSFus-pw-G
ProPEX LF Brass Sweat Adapter, 3/4" PEX x 3/4" Copper	LF4517575		UL 1821	cNSFus-pw-fs-G
ProPEX LF Brass Sweat Adapter, 1" PEX x 1" Copper	LF4511010		UL 1821	cNSFus-pw-fs-G
ProPEX LF Brass Sweat Adapter, 1 1/4" PEX x 1 1/4" Copper	LF4511313		UL 1821	cNSFus-pw-fs-G
ProPEX LF Brass Sweat Adapter, 1/2" PEX x 3/4" Copper	LF4515075			cNSFus-pw-G
ProPEX LF Brass Sweat Adapter, 1/2" PEX x 1/2" Copper	LF4515050			cNSFus-pw-G
ProPEX LF Brass Sweat Adapter, 3/4" PEX x 1/2" Copper	LF4517550			cNSFus-pw-G
ProPEX LF Brass Sweat Adapter, 3/4" PEX x 1" Copper	LF4517510			cNSFus-pw-G
ProPEX LF Brass Sweat Adapter, 1 1/2" PEX x 1 1/2" Copper	LF4511515			cNSFus-pw-G
ProPEX LF Brass Sweat Adapter, 2" PEX x 2" Copper	LF4512020			cNSFus-pw-G
ProPEX LF Brass Sweat Adapter, 2 1/2" PEX x 2 1/2" Copper	LF4512525			cNSFus-pw-G
ProPEX LF Brass Sweat Adapter, 3" PEX x 3" Copper	LF4513030			cNSFus-pw-G

L'installation

Use the appropriate Uponor ProPEX rings for the tubing (sold separately). Do not solder within 18" of ProPEX fittings. Refer to the AquaPEX® Professional Plumbing Installation Guide, Radiant Floor Heating Installation Handbook or AquaSAFETM Residential Fire Sprinkler Installation Guide for additional information.

Applications connexes

Radiant Heating and Cooling Systems

Permafrost Protection Systems

Turf Conditioning Systems

AquaSAFE™ Fire Safety Systems

Notes de bas de page

-

Coordonnées de la personne-ressource

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517

© 2024 Uponor Amérique du Nord. Tous droits réservés