

Adaptateurs coudés ProPEX en laiton sans plomb (LF) pour gicleur d'incendie



Renseignements sur le projet

| | |
|-----------------------------|---------------------|
| Nom du poste : | Lieu : |
| Ingénieur : | Date de soumission: |
| Entrepreneur : | Présentée par: |
| Représentant du fabricant : | Approuvé par : |

Données techniques

| | |
|-------------------------|--|
| Material | LF Brass |
| End type 2 | FNPT 1/2" |
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar) |
| Prop 65 label required? | Yes |

Informations sur le produit et utilisation de l'application

ProPEX® lead-free (LF) brass fire sprinkler adapter elbows are designed for use with 3/4" or 1" Uponor AquaPEX® tubing to connect fire sprinklers to the Uponor residential AquaSAFE™ fire safety system. Use Uponor ProPEX fittings for the connections.¹



| Nom de la pièce | Numéro de pièce | A [inch] | B [inch] | C [inch] | D [inch] | E [inch] | F [inch] | G [inch] | End Type 1 | Weight per UOM [lbs/UOM] |
|--|-----------------|----------|----------|----------|----------|----------|----------|----------|-------------|--------------------------|
| ProPEX LF Brass Fire Sprinkler Adapter Elbow, 3/4" PEX x 1/2" FNPT | LF7717550 | 0.945 | 0.865 | 1.115 | 2.675 | 2.209 | 1.46 | 0.73 | ProPEX 3/4" | 0.55 |
| ProPEX LF Brass Fire Sprinkler Adapter Elbow, 1" PEX x 1/2" FNPT | LF7711050 | 1.181 | 0.865 | 1.115 | 2.911 | 2.209 | 1.46 | 0.73 | ProPEX 1" | 0.59 |

| Nom de la pièce | Numéro de pièce | Les codes | Normes | Annonces |
|---|-----------------|------------------------------------|---|--|
| Adaptateurs coudés ProPEX en laiton sans plomb (LF) pour gicleur d'incendie | All | UPC IRC IPC NPC of Canada NSPC IMC | ASTM F877 NSF/ANSI/CAN 372 NSF/ANSI 359 ASTM F1960 CSA B137.5 UL 1821 NSF/ANSI/CAN 61 NSF/ANSI 14 | IAPMO-ES ICC-ES-PMG cNSFus-pw-G U.P.Code |

L'installation

Use the appropriate Uponor ProPEX ring for the tubing. Install the elbow using the Fire Sprinkler Adapter Mounting Bracket (A7750700) and Fire Sprinkler Adapter Push-on Nut (F7000005). For more information, refer to the Uponor AquaSAFE system installation guide

Applications connexes

PEX-a Plumbing Systems
AquaSAFE™ Fire Safety Systems

Notes de bas de page

Coordonnées de la personne-ressource

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517