

Adaptateurs de compression sur tube en cuivre ProPEX en laiton sans plomb (LF)



Renseignements sur le projet

| | |
|-----------------------------|---------------------|
| Nom du poste : | Lieu : |
| Ingénieur : | Date de soumission: |
| Entrepreneur : | Présentée par: |
| Représentant du fabricant : | Approuvé par : |

Données techniques

| | |
|-------------------------|--|
| Material | LF Brass |
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar) |
| Prop 65 label required? | Yes |

Informations sur le produit et utilisation de l'application

Uponor ProPEX®1 lead-free (LF) brass copper press adapters transition copper pipe to Uponor PEX. The adapters are approved for use in hot and cold potable water and hydronic heating and cooling systems.



| Nom de la pièce | Numéro de pièce | A [inch] | B [inch] | C [inch] | D [inch] | E [inch] | F [inch] | G [inch] | Cv | Weight per UOM [lbs/UOM] | Equivalent length branch [ft] |
|--|-----------------|----------|----------|----------|----------|----------|----------|----------|-------|--------------------------|-------------------------------|
| ProPEX LF Brass Copper Press Adapter, 1" PEX x 1" Copper | LFP4511010 | 2.677 | 0.315 | 1.181 | 1.134 | 1.516 | 0.63 | 1.181 | 22.1 | 0.28 | - |
| ProPEX LF Brass Copper Press Adapter, 1 1/4" PEX x 1 1/4" Copper | LFP4511313 | 3.051 | 0.583 | 1.024 | 1.39 | 1.89 | 0.76 | 1.445 | 34 | 0.48 | - |
| ProPEX LF Brass Copper Press Adapter, 1 1/2" PEX x 1 1/2" Copper | LFP4511515 | 3.602 | 0.559 | 1.339 | 1.64 | 2.193 | 0.902 | 1.705 | 45.5 | 0.74 | - |
| ProPEX LF Brass Copper Press Adapter, 2" PEX x 2" Copper | LFP4512020 | 4.646 | 0.492 | 2.008 | 2.138 | 2.717 | 1.152 | 2.146 | 83.6 | 1.3 | - |
| ProPEX LF Brass Copper Press Adapter, 2 1/2" PEX x 2 1/2" Copper | LFP4512525 | 5.217 | 0.654 | 1.732 | 2.642 | 3.366 | 1.585 | 2.831 | 136.2 | 2.38 | - |
| ProPEX LF Brass Copper Press Adapter, 3" PEX x 3" Copper | LFP4513030 | 6.142 | 0.831 | 1.929 | 3.15 | 3.799 | 1.844 | 3.382 | 189.1 | 3.42 | - |
| ProPEX LF Brass Copper Press Adapter, 1/2" PEX x 1/2" Copper | LFP4515050 | 2.185 | 0.571 | 0.906 | 0.634 | 0.965 | 0.38 | 0.709 | 5.7 | 0.1 | - |
| ProPEX LF Brass Copper Press Adapter, 3/4" PEX x 3/4" Copper | LFP4517575 | 2.52 | 0.709 | 0.866 | 0.886 | 1.236 | 0.502 | 0.945 | 13.4 | 0.18 | 0.99 |

| Nom de la pièce | Numéro de pièce | Equivalent length through [ft] | End Type 1 | End Type 2 |
|--|-----------------|--------------------------------|---------------|---------------------|
| ProPEX LF Brass Copper Press Adapter, 1" PEX x 1" Copper | LFP4511010 | 2.4 | ProPEX 1" | Copper Press 1" |
| ProPEX LF Brass Copper Press Adapter, 1 1/4" PEX x 1 1/4" Copper | LFP4511313 | 3.9 | ProPEX 1-1/4" | Copper Press 1-1/4" |
| ProPEX LF Brass Copper Press Adapter, 1 1/2" PEX x 1 1/2" Copper | LFP4511515 | 4.3 | ProPEX 1-1/2" | Copper Press 1-1/2" |
| ProPEX LF Brass Copper Press Adapter, 2" PEX x 2" Copper | LFP4512020 | 5.3 | ProPEX 2" | Copper Press 2" |
| ProPEX LF Brass Copper Press Adapter, 2 1/2" PEX x 2 1/2" Copper | LFP4512525 | 6.89 | ProPEX 2-1/2" | Copper Press 2-1/2" |
| ProPEX LF Brass Copper Press Adapter, 3" PEX x 3" Copper | LFP4513030 | 8.79 | ProPEX 3" | Copper Press 3" |
| ProPEX LF Brass Copper Press Adapter, 1/2" PEX x 1/2" Copper | LFP4515050 | 2 | ProPEX 1/2" | Copper Press 1/2" |
| ProPEX LF Brass Copper Press Adapter, 3/4" PEX x 3/4" Copper | LFP4517575 | 2.1 | ProPEX 3/4" | Copper Press 3/4" |

| L'installation | Applications connexes |
|----------------|-----------------------|
|----------------|-----------------------|

Use ProPEX tool and ProPEX rings (sold separately) for connecting the PEX pipe. For more information, refer to the Uponor Piping Pocket Guide. Follow press tool manufacturers' install instructions for the male or female press end of the adapter.

PEX-a Plumbing Systems
Hydronic heating and cooling systems
Permafrost Protection Systems

| Les codes | Normes | Annonces |
|-----------|--------|----------|
|-----------|--------|----------|

UPC|IBC|IRC|IPC|NPC of Canada|UMC|NSPC|IMC

ASME B16.51|IAPMO PS 117|NSF-372|ASTM F877|ICC-ES
LC1002|ASTM F1960|CSA B137.5|NSF-61|NSF-14

IAPMO-ES|cNSFus-pw-G|U.P.Code|ICC-PMG-1412

| Notes de bas de page | Coordonnées de la personne-ressource |
|----------------------|--------------------------------------|
|----------------------|--------------------------------------|

-

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517