

Adaptateur de raccord ProPEX en laiton

Renseignements sur le projet

| | |
|-----------------------------|---------------------|
| Nom du poste : | Lieu : |
| Ingénieur : | Date de soumission: |
| Entrepreneur : | Présentée par: |
| Représentant du fabricant : | Approuvé par : |

Données techniques

| | |
|-------------------------|--|
| Material | Brass |
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar) |
| Prop 65 label required? | Yes |

Informations sur le produit et utilisation de l'application

ProPEX® Brass Fitting Adapters transition crosslinked polyethylene (PEX) tubing to copper fittings. 1 These adapters are approved for use in hydronic radiant heating systems. One end of the adapter is manufactured with the Uponor ProPEX Fitting for connections to Wirsbo hePEX™ tubing. These adapters are safe for direct burial in soil.



| Nom de la pièce | Numéro de pièce | A [Inch] | B [Inch] | C [Inch] | D [Inch] | E [Inch] | F [Inch] | G [Inch] | Cv | Weight per UOM [lbs/UOM] | Equivalent length through [ft] |
|--|-----------------|----------|----------|----------|----------|----------|----------|----------|-------|--------------------------|--------------------------------|
| ProPEX Brass Fitting Adapter, 5/8" PEX x 1/2" Copper | Q4506350 | 1.551 | 0.125 | 0.56 | 0.624 | 0.94 | 0.312 | 0.866 | - | 0.06 | - |
| ProPEX Brass Fitting Adapter, 5/8" PEX x 3/4" Copper | Q4506375 | 1.801 | 0.125 | 0.81 | 0.874 | 0.94 | 0.437 | 0.866 | - | 0.11 | - |
| ProPEX Brass Fitting Adapter, 1" PEX x 1" Copper | Q5501010 | 2.276 | 0.125 | 0.97 | 1.125 | 1.36 | 0.563 | 1.181 | 30.5 | 0.19 | 1.3 |
| ProPEX Brass Fitting Adapter, 1 1/4" PEX x 1 1/4" Copper | Q5501313 | 2.6 | 0.125 | 1.03 | 1.375 | 1.72 | 0.687 | 1.445 | 34 | 0.33 | 3.8 |
| ProPEX Brass Fitting Adapter, 1 1/2" PEX x 1 1/2" Copper | Q5501515 | 2.989 | 0.125 | 1.16 | 1.625 | 1.9 | 0.813 | 1.704 | 63.7 | 0.46 | 1.8 |
| ProPEX Brass Fitting Adapter, 2" PEX x 2" Copper | Q5502020 | 3.807 | 0.25 | 1.41 | 2.125 | 2.68 | 1.063 | 2.147 | 150.7 | 1.08 | 0.8 |
| ProPEX Brass Fitting Adapter, 1/2" PEX x 1/2" Copper | Q5505050 | 1.394 | 0.125 | 0.56 | 0.625 | 0.77 | 0.313 | 0.709 | 7.7 | 0.06 | 1 |
| ProPEX Brass Fitting Adapter, 3/4" PEX x 1" Copper | Q5507510 | 2.04 | 0.11 | 0.985 | 1.125 | 1.15 | 0.563 | 0.945 | 11.4 | 0.14 | 3.1 |
| ProPEX Brass Fitting Adapter, 3/4" PEX x 1/2" Copper | Q5507550 | 1.63 | 0.125 | 0.56 | 0.624 | 1.1 | 0.312 | 0.945 | 8.8 | 0.09 | 1.5 |
| ProPEX Brass Fitting Adapter, 3/4" PEX x 3/4" Copper | Q5507575 | 1.88 | 0.125 | 0.81 | 0.874 | 1.1 | 0.437 | 0.945 | 15.7 | 0.11 | 1.5 |

| Nom de la pièce | Numéro de pièce | End Type 1 | End Type 2 |
|--|-----------------|---------------|--------------|
| ProPEX Brass Fitting Adapter, 5/8" PEX x 1/2" Copper | Q4506350 | ProPEX 5/8" | Sweat 1/2" |
| ProPEX Brass Fitting Adapter, 5/8" PEX x 3/4" Copper | Q4506375 | ProPEX 5/8" | Sweat 3/4" |
| ProPEX Brass Fitting Adapter, 1" PEX x 1" Copper | Q5501010 | ProPEX 1" | Sweat 1" |
| ProPEX Brass Fitting Adapter, 1 1/4" PEX x 1 1/4" Copper | Q5501313 | ProPEX 1-1/4" | Sweat 1-1/4" |
| ProPEX Brass Fitting Adapter, 1 1/2" PEX x 1 1/2" Copper | Q5501515 | ProPEX 1-1/2" | Sweat 1-1/2" |
| ProPEX Brass Fitting Adapter, 2" PEX x 2" Copper | Q5502020 | ProPEX 2" | Sweat 2" |
| ProPEX Brass Fitting Adapter, 1/2" PEX x 1/2" Copper | Q5505050 | ProPEX 1/2" | Sweat 1/2" |
| ProPEX Brass Fitting Adapter, 3/4" PEX x 1" Copper | Q5507510 | ProPEX 3/4" | Sweat 1" |
| ProPEX Brass Fitting Adapter, 3/4" PEX x 1/2" Copper | Q5507550 | ProPEX 3/4" | Sweat 1/2" |
| ProPEX Brass Fitting Adapter, 3/4" PEX x 3/4" Copper | Q5507575 | ProPEX 3/4" | Sweat 3/4" |

L'installation**Applications connexes**

ProPEX Tool and ProPEX Rings (sold separately) are required for connecting the PEX tubing. Do not solder within 18 inches of the ProPEX Fitting. For more information, refer to the Uponor Radiant Floor Heating Installation Handbook.

Radiant Heating and Cooling Systems

Les codes**Normes****Annonces**

IMC|BC|IRC|NPC of Canada|UMC

ASTM F1960|CSA B137.5|NSF-14|ASTM F877

IAPMO-ES|ICC-ES-PMG|cNSFus-rfh

Notes de bas de page**Coordonnées de la personne-ressource**

-

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517