

Valves ProPEX pour compteur d'eau en laiton sans plomb (LF)



Renseignements sur le projet

| | |
|-----------------------------|---------------------|
| Nom du poste : | Lieu : |
| Ingénieur : | Date de soumission: |
| Entrepreneur : | Présentée par: |
| Représentant du fabricant : | Approuvé par : |

Données techniques

| | |
|-------------------------|--|
| Material | LF Brass |
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar) |
| Prop 65 label required? | Yes |

Informations sur le produit et utilisation de l'application

Use Uponor ProPEX® lead-free (LF) brass water meter service valves in all commercial submetering and residential water service inlets, outlets or both. The valves allow for a direct ASTM F1960 connection to water meters sized 5/8" to 1". Valve is sized for 3/4" or 1" Uponor AquaPEX® tubing. Product handle material is stainless steel.



| Nom de la pièce | Numéro de pièce | A [inch] | B [inch] | C [inch] | D [inch] | E [inch] | F [inch] | G [inch] | H [inch] | I [inch] | J [inch] |
|--|-----------------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|
| ProPEX LF Brass Straight Water Meter Valve, 3/4" PEX x 1" NPSM | WS4820750 | 0.945 | 2.957 | 1.551 | 2.992 | 0.591 | 1.9 | 1.299 | 4.278 | 2.501 | 5.734 |
| ProPEX LF Brass Elbow Water Meter Valve, 3/4" PEX x 1" NPSM | WS4820751 | 0.945 | 2.249 | 1.551 | 2.992 | 0.781 | 1.9 | 1.299 | 0.65 | 3.277 | 5.735 |
| ProPEX LF Brass Straight Water Meter Valve, 1" PEX x 1 1/4" NPSM | WS4821000 | 1.181 | 3.302 | 2.015 | 3.819 | 0.677 | 2.25 | 1.614 | 5.158 | 3.139 | 7.119 |
| ProPEX LF Brass Elbow Water Meter Valve, 1" PEX x 1 1/4" NPSM | WS4821001 | 1.181 | 2.625 | 2.015 | 3.819 | 0.827 | 2.25 | 1.614 | 0.807 | 4.022 | 7.119 |

| Nom de la pièce | Numéro de pièce | K [inch] | Cv | Weight per UOM [lbs/UOM] | End Type 1 | End Type 2 |
|--|-----------------|----------|------|--------------------------|-------------|-------------|
| ProPEX LF Brass Straight Water Meter Valve, 3/4" PEX x 1" NPSM | WS4820750 | 0.65 | 10.9 | 0.76 | ProPEX 3/4" | NPSM 1" |
| ProPEX LF Brass Elbow Water Meter Valve, 3/4" PEX x 1" NPSM | WS4820751 | 0.65 | 4.9 | 0.76 | ProPEX 3/4" | NPSM 1" |
| ProPEX LF Brass Straight Water Meter Valve, 1" PEX x 1 1/4" NPSM | WS4821000 | 0.807 | 18.7 | 1.22 | ProPEX 1" | NPSM 1-1/4" |
| ProPEX LF Brass Elbow Water Meter Valve, 1" PEX x 1 1/4" NPSM | WS4821001 | 0.807 | 9.7 | 1.24 | ProPEX 1" | NPSM 1-1/4" |

L'installation

ProPEX tool and ProPEX rings (sold separately) are required for connecting the PEX tubing. For more information, refer to the Uponor Residential Plumbing Systems Installation Guide or the Uponor Piping Systems Installation Guide.

Applications connexes

PEX-a Plumbing Systems

Les codes

UPC|IBC|IRC|IPC|NPC of Canada|UMC|NSPC|IMC

Normes

NSF-372|ASTM F877|NSF-359|ASTM F1960|CSA B137.5|NSF-61|NSF-14

Annonces

HUD MR 1269|cNSFus-pw-G|U.P.Code

Notes de bas de page

Coordonnées de la personne-ressource

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517