

Collecteurs sans vanne en cuivre (type L)

Renseignements sur le projet

|                             |                     |
|-----------------------------|---------------------|
| Nom du poste :              | Lieu :              |
| Ingénieur :                 | Date de soumission: |
| Entrepreneur :              | Présentée par:      |
| Représentant du fabricant : | Approuvé par :      |

Données techniques

|                         |                                                                                                                                                        |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Material                | Copper                                                                                                                                                 |
| Temp/pressure ratings   | 73 °F (23 °C) at 160 psi (11 bar)<br>180 °F (82 °C) at 100 psi (6.9 bar)<br>200 °F (93 °C) at 80 psi (5.5 bar)<br>210 °F (99 °C) at 149 psi (10.3 bar) |
| Prop 65 label required? | Yes                                                                                                                                                    |

Informations sur le produit et utilisation de l'application

Use the Uponor 2" Copper Valveless Manifold in hot and cold domestic potable water distribution systems or balanced radiant heating and/or cooling systems that do not require individual loop control. The manifold features ¾" sweat connections



| Nom de la pièce                                                       | Numéro de pièce | End Type 1 |
|-----------------------------------------------------------------------|-----------------|------------|
| 2" x 6' Copper Valveless Manifold with 24 outlets, 3/4" sweat         | F2802075        | Sweat 3/4" |
| 1 1/2" x 6' Copper Valveless Manifold with 24 outlets, 3/4" sweat     | F2801575        | Sweat 3/4" |
| 1" Copper Valveless Manifold, 3 outlets, 1/2" sweat, 1 1/2" on center | F2751050        | Sweat 1/2" |
| 1" Copper Valveless Manifold, 4 outlets, 1/2" sweat, 1 1/2" on center | F2761050        | Sweat 1/2" |

| Nom de la pièce                                                                 | Numéro de pièce | Les codes                  | Normes               | Annonces                                              |
|---------------------------------------------------------------------------------|-----------------|----------------------------|----------------------|-------------------------------------------------------|
| Collecteurs sans vanne en cuivre (type L)                                       | All             | UPC IPC NPC of Canada NSPC | ASTM F877 CSA B137.5 | -                                                     |
| In addition, the following parts have additional codes, standards, or listings: |                 |                            |                      |                                                       |
| 2" x 6' Copper Valveless Manifold with 24 outlets, 3/4" sweat                   | F2802075        |                            |                      | NSF 14- and 61-certified                              |
| 1 1/2" x 6' Copper Valveless Manifold with 24 outlets, 3/4" sweat               | F2801575        |                            |                      | NSF 14- and 61-certified                              |
| 1" Copper Valveless Manifold, 3 outlets, 1/2" sweat, 1 1/2" on center           | F2751050        |                            | NSF-61 NSF-14        | ICC-ES-PMG IAPMO 3946 cNSFus-pw-G CSA B137.5 U.P.Code |
| 1" Copper Valveless Manifold, 4 outlets, 1/2" sweat, 1 1/2" on center           | F2761050        |                            | NSF-61 NSF-14        | ICC-ES-PMG IAPMO 3946 cNSFus-pw-G CSA B137.5 U.P.Code |

| L'installation                                                                                                                                                                                                         | Applications connexes                                         |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------|
| Use any product designed to mount 2" copper pipe as a mounting bracket. Any bend within 6 inches of the connection to the manifold requires the use of a tube talon (F7050750) or bend supports (A5110750 or A5150750) | PEX-a Plumbing Systems<br>Radiant Heating and Cooling Systems |

| Notes de bas de page | Coordonnées de la personne-ressource                                                                                                                                                                   |
|----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| -                    | Uponor Inc.<br>5925 148th Street West<br>Apple Valley, MN 55124<br>T 800.321.4739<br>F 952.891.2008<br>Uponor Ltd.<br>6510 Kennedy Road<br>Mississauga, ON L5T 2X4<br>T 888.594.7726<br>F 800.638.9517 |