

# Corps de valve d'isolation pour collecteur en acier inoxydable



## Renseignements sur le projet

Nom du poste :	Lieu :
Ingénieur :	Date de soumission:
Entrepreneur :	Présentée par:
Représentant du fabricant :	Approuvé par :

## Données techniques

Material	Brass
Subcomponent Material	Axle material (valve body): Brass CW614N-UNI EN 12164 Axle material (cap): Acrylonitrile butadiene styrene (ABS) plastic Spring material (valve body): Stainless steel O-ring material (valve body):
Temp/pressure ratings	68 °F (20 °C) at 145 psi (10 bar) 158 °F (70 °C) at 87 psi (6 bar) 194 °F (90 °C) at 44 psi (3 bar)
Prop 65 label required?	Yes



## Informations sur le produit et utilisation de l'application

Uponor's Stainless-steel Manifolds all come standard with isolation valves for easy loop isolation. These components are fixed to the return side of the manifold and are used to shut off the flow of water or water/glycol mix through the manifold port.

Nom de la pièce	Numéro de pièce	C [inch]	Weight per UOM [lbs/UOM]
Stainless-steel Manifold Isolation Valve Body, replacement part	A2771030	2.18	0.15
O-ring for Stainless-steel Manifold Isolation Valve Body	A2771035	0.669	0

## L'installation

To operate the isolation valve on the Uponor Stainless-steel Manifold, twist the Stainless-steel Manifold On/Off Valve Plastic Cap clockwise to close and counterclockwise to open. For more information, refer to the Uponor Stainless-steel Manifold Installation Guide.

## Applications connexes

Radiant Heating and Cooling Systems  
Permafrost Protection Systems  
Turf Conditioning Systems

## Remarques :

Maximum test pressure:  
145 psi

## Notes de bas de page

## Coordonnées de la personne-ressource

Uponor Inc.  
5925 148th Street West  
Apple Valley, MN 55124  
T 800.321.4739  
F 952.891.2008

Uponor Ltd.  
6510 Kennedy Road  
Mississauga, ON L5T 2X4  
T 888.594.7726  
F 800.638.9517