Corps de valve d'isolation pour collecteur en acier inoxydable

Renseignements sur le projet

Nom du poste :	Lieu :
Ingénieur :	Date de soumission:
Entrepreneur :	Présentée par:
Représentant du fabricant :	Approuvé par :

Données techniques

Temp/pressure ratings	68 °F (20 °C) at 145 psi (10 bar) 158 °F (70 °C) at 87 psi (6 bar) 194 °F (90 °C) at 44 psi (3 bar)
Prop 65 label required?	Yes



Informations sur le produit et utilisation de l'application

Uponor's Stainless-steel Manifolds all come standard with isolation valves for easy loop isolation. These components are fixed to the return side of the manifold and are used to shut off the flow of water or water/glycol mix through the manifold port.

	Nom de la pièce	Numéro de pièce	C [inch]	Material group	Subcomponent Material	Weight per UOM [lbs/UOM]
✔	Stainless-steel Manifold Isolation Valve Body, replacement part	A2771030	2.18	Brass	Axle material (valve body): Brass CW614N-UNI EN 12164 Axle material (cap): Acrylonitrile butadiene styrene (ABS) plastic Spring material (valve body): Stainless steel O-ring material (valve body):	0.15
	O-ring for Stainless-steel Manifold Isolation Valve Body	A2771035	-	Rubber	-	0

L'installation

To operate the isolation valve on the Uponor Stainless-steel Manifold, twist the Stainless-steel Manifold On/Off Valve Plastic Cap clockwise to close and counterclockwise to open. For more information, refer to the Uponor Stainless-steel Manifold Installation Guide.

Applications connexes

Radiant Heating and Cooling Systems

Permafrost Protection Systems

Turf Conditioning Systems

Remarques :

Maximum test pressure:
145 psi

Notes de bas de page

-

Coordonnées de la personne-ressource

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726

© 2026 Uponor Amérique du Nord. Tous droits réservés