

Vannes mélangeuses thermiques

Renseignements sur le projet

Nom du poste :

Lieu :

Ingénieur :

Date de
soumission:

Entrepreneur :

Présentée par:

Représentant du fabricant :

Approuvé par :

Données techniques

Material Brass

Informations sur le produit et utilisation de l'application

Thermal mixing valves thermostatically control water temperatures between 104°F to 167°F (40°C to 75°C). These non-corrosive, reactive valves come with 1" sweat connections.



Nom de la pièce	Numéro de pièce	Subcomponent Material	Operating Temperature 1 [°F]	Operating Temperature 2 [°F]	Operating Temperature 3 [°F]	Prop 65 label required?	A [inch]	B [inch]	C [inch]	Weight per UOM [lbs/UOM]
-----------------	-----------------	-----------------------	------------------------------	------------------------------	------------------------------	-------------------------	----------	----------	----------	--------------------------

1" Thermal Mixing Valve with Union	A5402112	Seals: EPDM	73	180	200	Yes	-	-	-	2.28
1" Union Replacement Gasket	A5400012	-	-	-	-	-	1.181	1.181	0.118	0

Nom de la pièce	Numéro de pièce	Les codes	Normes	Annonces
Vannes mélangeuses thermiques	All	-	ASSE 1016-T ASSE 1017	-

L'installation	Applications connexes
----------------	-----------------------

This product should be installed by qualified personnel in accordance with local codes and ordinances. It is the responsibility of the installer to properly select, install and adjust this device as specified in the instructions enclosed with the product.

Radiant Heating and Cooling Systems

Remarques :

Mixed outlet temperature 104°F to 167°F (40°C to 75°C)
Working pressure: 30 to 150 psi (2 to 10 bar)
Maximum relationship between the inlet pressure: 2:1
Minimum flow rate: 1.6gpm

Notes de bas de page	Coordonnées de la personne-ressource
----------------------	--------------------------------------

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517