

# Débitmètres pour collecteur en acier inoxydable

## Renseignements sur le projet

Nom du poste :	Lieu :
Ingénieur :	Date de soumission:
Entrepreneur :	Présentée par:
Représentant du fabricant :	Approuvé par :

## Données techniques

Temp/pressure ratings	68 °F (20 °C) at 145 psi (10 bar) 158 °F (70 °C) at 87 psi (6 bar) 194 °F (90 °C) at 44 psi (3 bar)
Prop 65 label required?	Yes

## Informations sur le produit et utilisation de l'application

Uponor's Stainless-steel Manifolds all come standard with balancing valves and flow meters. These components are fixed to the supply side of the manifold and are used to balance and correct the flow of water or water/glycol mix through the manifold.



Nom de la pièce	Numéro de pièce	Weight per UOM [lbs/UOM]
Stainless-steel Manifold Flow Meter 1.5 GPM Valve Body, replacement part	A2771020	0.13
Stainless-steel Manifold Flow Meter 2 GPM Valve Body, replacement part	A2771021	0.13

## L'installation

To operate the flow meter, remove the plastic cover by pulling up, then rotate the flow meter either clockwise to restrict flow or counterclockwise to open. Once desired location is achieved, replace the plastic cap to lock the flow meter back in place. For more information, refer to the Uponor Stainless-steel Manifold Installation Guide.

## Applications connexes

- Radiant Heating and Cooling Systems
- Permafrost Protection Systems
- Turf Conditioning Systems
- AquaSAFE™ Fire Safety Systems

## Remarques :

Maximum test pressure:  
145 psi

## Notes de bas de page

## Coordonnées de la personne-ressource

-	<p>Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008</p>	<p>Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517</p>
---	--	--