Trousses d'extension pour collecteur TruFLOW Classic

Renseignements sur le projet

Nom du poste :	Lieu :
Ingénieur :	Date de soumission:
Entrepreneur :	Présentée par:
Représentant du fabricant :	Approuvé par :

Données techniques

Material	Brass
Manifold size	1.25 inch
Loop Cv	1.9 Cv
End type 1	ISO 228-G 1-1/4"
End type 2	ISO 228-G 3/4"
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)
Max. fluid flow rate	21 gpm
Prop 65 label required?	Yes



Informations sur le produit et utilisation de l'application

The Uponor TruFLOW™ Classic Manifold Extension Kit is designed for easy, inline extension of up to two additional loops for the TruFLOW Classic Manifold Assembly. The kit contains two 1¼" BSP nipples, one supply manifold, one return manifold and two loop end caps. Use silicone oil lubricant on the male threads to ease installation.

Nom de la pièce	Numéro de pièce	Weight per UOM [kg/UOM]
TruFLOW Classic Manifold Extension Kit, 2 loops	A2610100	2.495

Nom de la pièce	Numéro de pièce	Les codes	Normes	Annonces
Trousses d'extension pour collecteur TruFLOW Classic	A2610100	-	R32: ISO 228-G 1¼"|ASTM F877|R20: ISO 228-G ¾"	-

L'installation

Use the supplied TruFLOW Classic Manifold Coupling Nipple to attach the TruFLOW Manifold Extension Kit to the desired TruFLOW Manifold. Use the TruFLOW Balancing Hex Key (A2620002) on the internal balancing valves of the supply manifold. Manifold is shipped with the appropriate number of TruFLOW Manifold Actuator Adapters (A2630028). Refer to the TruFLOW Classic Manifold Instruction Sheet for further information.

Applications connexes

Radiant Heating and Cooling Systems

Permafrost Prevention Systems

Turf Conditioning Systems

Remarques :

Manifold loop threaded connections:
ISO 228-G ¾" (R20)

Notes de bas de page

-

Coordonnées de la personne-ressource

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517

© 2024 Uponor Amérique du Nord. Tous droits réservés