

Rouleaux blancs Uponor AquaPEX à imprimé rouge

Renseignements sur le projet

Nom du poste :	Lieu :
Ingénieur :	Date de soumission:
Entrepreneur :	Présentée par:
Représentant du fabricant :	Approuvé par :

Données techniques

Material	PEX
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)

Informations sur le produit et utilisation de l'application

Uponor AquaPEX® white tubing with red print is an Engel-method, PEX-a pipe designed for hot potable water distribution systems, but can also be used in radiant heating and cooling systems containing no ferrous corrodible components or where ferrous components are isolated from the tubing

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.



Nom de la pièce	Numéro de pièce	Inner diameter coil [mm]	Outer diameter coil [mm]	Inner diameter pipe [mm]	Outer diameter pipe [mm]	Weight per UOM [kg/UOM]
1/2" Uponor AquaPEX White, Red Print, 100-ft. coil	F4240500	400.05	596.9	12.07	15.88	2.722
3/4" Uponor AquaPEX White, Red Print, 100-ft. coil	F4240750	400.05	812.8	17.04	22.22	4.536
1/2" Uponor AquaPEX White, Red Print, 300-ft. coil	F4260500	500.38	812.8	12.07	15.88	8.165
3/4" Uponor AquaPEX White, Red Print, 300-ft. coil	F4260750	558.8	812.8	17.04	22.22	15.422
1" Uponor AquaPEX White, Red Print, 100-ft. coil	F4241000	576.58	812.8	21.9	28.58	9.072
1" Uponor AquaPEX White, Red Print, 300-ft. coil	F4261000	576.58	812.8	21.9	28.58	25.401
1/2" Uponor AquaPEX White, Red Print, 1000-ft. coil	F4220500	400.05	812.8	12.07	15.88	24.494

Nom de la pièce	Numéro de pièce	Les codes	Normes	Annonces
Rouleaux blancs Uponor AquaPEX à imprimé rouge	All	IMC UPC IBC IRC NBC of Canada IPC UFGS NPC of Canada UMC NSPC	ASTM F1960 ASTM E119 UL 263 ASTM F876 ASTM E84 ASTM F2023 ASTM E814 ULC S115 ASTM F877 CSA B137.5 ULC S102.2 CSA B214 ULC S101	IAPMO-ES ICC-ES-PMG cNSFus-pw CCMC PPI TR-4 CSA UL U.P.Code cQAlus P321 HUD MR 1269 BMEC
In addition, the following parts have additional codes, standards, or listings:				
1/2" Uponor AquaPEX White, Red Print, 100-ft. coil	F4240500		NSF-61 NSF-14	
3/4" Uponor AquaPEX White, Red Print, 100-ft. coil	F4240750		NSF/ANSI/CAN 61 NSF/ANSI 14	
1/2" Uponor AquaPEX White, Red Print, 300-ft. coil	F4260500		NSF/ANSI/CAN 61 NSF/ANSI 14	
3/4" Uponor AquaPEX White, Red Print, 300-ft. coil	F4260750		NSF/ANSI/CAN 61 NSF/ANSI 14	
1" Uponor AquaPEX White, Red Print, 100-ft. coil	F4241000		NSF/ANSI/CAN 61 NSF/ANSI 14	
1" Uponor AquaPEX White, Red Print, 300-ft. coil	F4261000		NSF-61 NSF-14	
1/2" Uponor AquaPEX White, Red Print, 1000-ft. coil	F4220500		NSF-61 NSF-14	

L'installation

Approved fitting system is ProPEX®1. Refer to the Uponor ProPEX Connections Instructional Guide, the Uponor Professional Plumbing Installation Guide or the Uponor Piping Pocket Guide for more information.

Applications connexes

PEX-a Plumbing Systems
Radiant Heating and Cooling Systems

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517
