Longueurs droites Wirsbo hePEX

Renseignements sur le projet

Nom du poste :	Lieu :
Ingénieur :	Date de soumission:
Entrepreneur :	Présentée par:
Représentant du fabricant :	Approuvé par :

Données techniques

Material	PEX
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)

Informations sur le produit et utilisation de l'application

Wirsbo hePEX™ tubing is used for closed-loop heating and cooling applications, including radiant and hydronic distribution. Wirsbo hePEX tubing has an EVOH oxygen diffusion barrier that meets German DIN 4726/9. A polyethylene layer extruded over the EVOH barrier protects tubing from site abuse and moisture saturation.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.



Nom de la pièce	Numéro de pièce	Inner diameter pipe [inch]	Outer diameter pipe [inch]	Bundle Diameter [in]	Bundle Length [in]	Weight per UOM [lbs/UOM]
1/2" Wirsbo hePEX, 20-ft. straight length, 500 ft. (25 per bundle)	A1930500	0.475	0.625	3.5	258	26.48
5/8" Wirsbo hePEX, 20-ft. straight length, 300 ft. (15 per bundle)	A1930625	0.574	0.75	4.5	258	22.79
3/4" Wirsbo hePEX, 20-ft. straight length, 300 ft. (15 per bundle)	A1930750	0.671	0.875	4.5	258	30.07
1" Wirsbo hePEX, 20-ft. straight length, 200 ft. (10 per bundle)	A1921000	0.862	1.125	4	258	34.19
1 1/4" Wirsbo hePEX, 20-ft. straight length, 100 ft. (5 per bundle)	A1921250	1.054	1.375	4.5	258	24.1
1 1/2" Wirsbo hePEX, 20-ft. straight length, 100 ft. (5 per bundle)	A1921500	1.244	1.625	5	258	34.93
2" Wirsbo hePEX, 20-ft. straight length, 100 ft. (5 per bundle)	A1922000	1.629	2.125	10.75	264	60.1
2 1/2" Wirsbo hePEX 20-ft. straight length, 60 ft.(3 per bundle)	A1922500	2.011	2.625	10.75	264	55.3
3" Wirsbo hePEX 20-ft. straight length, 40 ft.(2 per bundle)	A1923000	2.398	3.125	10.75	264	51.9

Nom de la pièce	Numéro de pièce	Les codes	Normes	Annonces
Longueurs droites Wirsbo hePEX	All	UPC|IMC|NBC of Canada|IPC|IBC|IRC|UMC|NSPC|UFGS|NPC of Canada	ASTM E119/UL 263|ASTM F1960|ASTM E84|ASTM F2023|ASTM E814/ULC S115|CSA B214|CSA B137.5|NSF/ANSI 14|NSF/ANSI/CAN 61|ASTM F876|ASTM F877|ULC S102.2|ULC S101	cNSFus-pw|IAPMO-ES|ICC-ES-PMG|CSA|CCMC|PPI TR-4|cQAIus P321|UL|U.P.Code|cNSFus-rfh

L'installation

Use ProPEX® fittings for pipe sizes to 3".1 Use WIPEX™ fittings for 3½" and 4" pipe. Refer to the Uponor Complete Design Assistance Manual (CDAM) or the Uponor Hydronic Piping Design Assistance Manual (HPDAM) for additional information.

Applications connexes

Radiant Heating and Cooling Systems

Permafrost Protection Systems

Turf Conditioning Systems

Chilled water distribution

Hot water distribution

Notes de bas de page

-

Coordonnées de la personne-ressource

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517

© 2026 Uponor Amérique du Nord. Tous droits réservés