

Embouts à évent

Renseignements sur le projet

Nom du poste :	Lieu :
Ingénieur :	Date de soumission:
Entrepreneur :	Présentée par:
Représentant du fabricant :	Approuvé par :

Données techniques

Material	Brass
Manifold size	1 inch
End type 1	ISO 228-G 1-1/4"
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)
Max. fluid flow rate	21 gpm
Prop 65 label required?	Yes

Informations sur le produit et utilisation de l'application

The End Cap with Vent, R32, caps the end of the TruFLOW™ Jr. modular manifolds. It comes complete with a swivel drain valve and a manual air vent. Includes required Manifold Gasket (A2403232).



Nom de la pièce	Numéro de pièce	A [mm]	B [mm]	C [mm]	Weight per UOM [kg/UOM]
End Cap with Vent, R32	A2803250	100	77.55	50	0.408

L'installation

Use with TruFLOW Jr. modular manifolds (not preassembled). Use the End Cap with Vent on the top manifold, following procedures outlined in the Uponor TruFLOW Jr. instruction sheet.

Applications connexes

Radiant Heating and Cooling Systems

Remarques :

Connection:
1¼" BSPP

Notes de bas de page

Coordonnées de la personne-ressource

-	Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008	Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517
---	--	--