Boîtiers pour machine à glaçons ProPEX en laiton sans plomb (LF) (en angle)

Renseignements sur le projet

Nom du poste :	Lieu :
Ingénieur :	Date de soumission:
Entrepreneur :	Présentée par:
Représentant du fabricant :	Approuvé par :

Données techniques

Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)

Informations sur le produit et utilisation de l'application

The ProPEX® Ice Maker Box with Support Brackets, ½" (LF Brass) Valve with snap-in frame includes a ½" lead-free brass valve with ¼" O.D. compression connection.1 This high-impact box is an aesthetic, convenient option for connecting to standard ice maker tubing. Two support brackets are provided for easy mounting.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.



Nom de la pièce	Numéro de pièce	A [inch]	B [inch]	C [inch]	Material group	End Type 1	End Type 2	Prop 65 label required?	Weight per UOM [lbs/UOM]
ProPEX Ice Maker Box with Support Brackets, 1/2" LF Brass Valve	LF5955025	20.29	6	3.55	-	ProPEX	Compression	Yes	0.87
1/4" Insert (stainless steel)	F5400250	0.719	0.323	0.323	Stainless Steel	-	-	-	0

Nom de la pièce	Numéro de pièce	Les codes	Normes	Annonces
Boîtiers pour machine à glaçons ProPEX en laiton sans plomb (LF) (en angle)	All	UPC|IPC|NPC of Canada	ASME A112.18.1|NSF/ANSI/CAN 372|ASTM F877|ASTM F1960|CSA B125|CSA B137.5|NSF/ANSI/CAN 61|NSF/ANSI 14	cNSFus-pw-G|U.P.Code

L'installation

Mount in wall cavity at the desired location (e.g., behind refrigerator) using the supplied mounting brackets or directly to studs. For more information, refer to the AquaPEX® Professional Plumbing Installation Guide.

Applications connexes

PEX-a Plumbing Systems

Notes de bas de page

-

Coordonnées de la personne-ressource

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517

© 2026 Uponor Amérique du Nord. Tous droits réservés