

Embouts de conversion de type QS

Renseignements sur le projet

Nom du poste :

Lieu :

Ingénieur :

Date de soumission:

Entrepreneur :

Présentée par:

Représentant du fabricant :


Approuvé par :

Données techniques

Material	Brass
End type 1	ISO 228-G 3/4"
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)
Prop 65 label required?	Yes

Informations sur le produit et utilisation de l'application

The Uponor QS-style Conversion Nipple fittings are available in various thread options and used with compression fittings to adapt to male national pipe thread (MNPT) in hydronic heating applications. Use the QS-style Conversion Nipple and the appropriate fitting to connect 5/16", 3/8", 1/2", 5/8" or 3/4" Uponor tubing to 1/2", 3/4" and 1" NPT.



Nom de la pièce	Numéro de pièce	A [inch]	B [inch]	C [inch]	D [inch]	End Type 2	Weight per UOM [lbs/UOM]
QS-style Conversion Nipple, R20 x 1/2" NPT	A4322050	1.536	1.227	1.063	-	MNPT 1/2"	0.18
QS-style Conversion Nipple, R20 x 3/4" NPT	A4322075	1.668	1.227	1.063	-	MNPT 3/4"	0.25

Nom de la pièce	Numéro de pièce	Les codes	Normes	Annonces
Embouts de conversion de type QS	All	-	ASTM F877 R20: ISO 228-G 3/4"	-

L'installation

The corresponding compression fitting threads onto the R20 or R25 thread to adapt to MNPT. For more information, refer to the Radiant Floor Heating Installation Handbook.

Applications connexes

- Radiant Heating and Cooling Systems
- Permafrost Protection Systems
- Turf Conditioning Systems

Notes de bas de page

Coordonnées de la personne-ressource

-	Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008	Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517
---	---	---