

Adaptateurs et raccords droits filetés pour collecteur en laiton



Renseignements sur le projet


Nom du poste :	Lieu :
Ingénieur :	Date de soumission:
Entrepreneur :	Présentée par:
Représentant du fabricant :	Approuvé par :

Données techniques

End type 1	ISO 228-G 1-1/4"
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)
Prop 65 label required?	Yes

Informations sur le produit et utilisation de l'application

Uponor's Threaded Brass Manifold Bushings are used in TruFLOW™ manifolds. In radiant heating applications, the bushing transitions the R32 manifold union nut to 1" national pipe thread (NPT) and 3/4" threaded connections (PEX or Multi-layer Composite (MLC) tubing with QS-style fittings).



Nom de la pièce	Numéro de pièce	Material group	End Type 2
Threaded Brass Manifold Straight Adapter, R32 Male x R20 Male	A4143220	Brass	ISO 228-G 3/4"
Threaded Brass Manifold Straight Adapter, R32 Male x R25 Male	A4143225	LF Brass	ISO 228-G 1"
Threaded Brass Manifold Bushing, R32 Male x 3/4" Female NPT	A2133275	Brass	FNPT 3/4"
Threaded Brass Manifold Bushing, R32 Male x 1" Female NPT	A2123210	Brass	FNPT 1"

Nom de la pièce	Numéro de pièce	Les codes	Normes	Annonces
Adaptateurs et raccords droits filetés pour collecteur en laiton	All	IMC IRC NBC of Canada UMC	CSA B137.5 R32: ISO 228-G 1 1/4" ASTM F877	cNSFus-rfh

L'installation	Applications connexes
Thread directly into Uponor TruFLOW manifolds. For additional information, refer to the TruFLOW Manifold Instruction Sheet or the Uponor Radiant Floor Heating Installation Handbook.	Radiant Heating and Cooling Systems Permafrost Protection Systems Turf Conditioning Systems

Notes de bas de page	Coordonnées de la personne-ressource
-	Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008 Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517