
# Tés verticaux multivoies ouverts en EP

## Renseignements sur le projet

| | |
|---|---|
| Nom du poste : | Lieu : |
| Ingénieur : | Date de soumission: |
| Entrepreneur : | Présentée par: |
| Représentant du fabricant : | Approuvé par : |

## Données techniques

| | |
|---|---|
| Material | Engineered Polymer |
| End type 1 | ProPEX 3/4" |
| End type 2 | ProPEX 3/4" |
| End type 3 | ProPEX 3/4" |
| End type 4 | ProPEX 1/2" |
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar)<br>180 °F (82 °C) at 100 psi (6.9 bar)<br>200 °F (93 °C) at 80 psi (5.5 bar) |




## Informations sur le produit et utilisation de l'application

Engineered polymer (EP) flow-through vertical multi-port tees are designed for use in hot and cold domestic potable water distribution systems. The tee features ¾" ProPEX® inlets and ½" ProPEX outlets.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.

| Nom de la pièce | Numéro de pièce | A [inch] | B [inch] | C [inch] | D [inch] | E [inch] | F [inch] | G [inch] | H [inch] | I [inch] | J [inch] |
|---|---|---|---|---|---|---|---|---|---|---|---|
| EP Flow-through Multi-port Vertical Tee, 3 (1/2") outlets, 3/4" x 3/4" x 3/4" ProPEX | Q2237757 | 6.17 | 0.955 | 4.625 | 0.625 | 1.25 | 0.467 | 0.719 | 2.845 | 1.18 | 0.955 |
| EP Flow-through Multi-port Vertical Tee, 4 (1/2") outlets, 3/4" x 3/4" x 3/4" ProPEX | Q2247757 | 7.42 | 0.955 | 5.875 | 0.625 | 1.25 | 0.467 | 0.719 | 2.845 | 1.18 | 0.955 |

| Nom de la pièce | Numéro de pièce | Cv Through | Cv Branch |
|---|---|---|---|
| EP Flow-through Multi-port Vertical Tee, 3 (1/2") outlets, 3/4" x 3/4" x 3/4" ProPEX | Q2237757 | 13.6 | 3.1 |
| EP Flow-through Multi-port Vertical Tee, 4 (1/2") outlets, 3/4" x 3/4" x 3/4" ProPEX | Q2247757 | - | 3.3 |

| Nom de la pièce | Numéro de pièce | Les codes | Normes | Annonces |
|---|---|---|---|---|
| Tés verticaux multivoies ouverts en EP | All | UPC\|IBC\|IRC\|IPC\|NPC of Canada\|UMC\|NSPC\|IMC | ASTM E814/ULC S115\|ASTM F877\|ASTM F1960\|CSA B137.5\|ULC S102.2\|ASTM E119/UL 263\|NSF/ANSI/CAN 61\|ULC S101\|NSF/ANSI 14 | IAPMO-ES\|HUD MR 1269\|ICC-ES-PMG\|cNSFus-pw\|UL\|U.P.Code\|cQAIus P321 |

## L'installation

Use any product designed to mount 1" copper pipe as a mounting bracket. For more information, refer to the Uponor Piping Systems Installation Guide

## Applications connexes

PEX-a Plumbing Systems

## Remarques :

Cv branch tee to branch #2 = 3.1
Cv through tee to tee = 13.6
Cv through tee to side = 7.4
Cv branch side to #2 = 3.6
Cv through side to tee = 6.9

## Notes de bas de page

-

## Coordonnées de la personne-ressource

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517

© 2026 Uponor Amérique du Nord. Tous droits réservés