

# Vannes thermiques par zone

## Renseignements sur le projet

Nom du poste :	Lieu :
Ingénieur :	Date de soumission:
Entrepreneur :	Présentée par:
Représentant du fabricant :	Approuvé par :

## Données techniques

Material	Brass
End type 1	Sweat 3/4"
End type 2	Sweat 1"
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)
Prop 65 label required?	Yes

## Informations sur le produit et utilisation de l'application

The Uponor Thermal Zone Valve, four-wire, features 3/4" and 1" sweat connections. It provides flow control for individual terminal units or a single-zone manifold (manifold serving one zone). The Thermal Zone Valve is assembled with the 1-watt Uponor Thermal Actuator, four-wire (A3023522) which includes an end switch for activation of a relay pump, heat plant or other auxiliary devices.



Nom de la pièce	Numéro de pièce	A [inch]	B [inch]	C [inch]	Cv	Weight per UOM [lbs/UOM]
3/4" and 1" Thermal Zone Valve	A3011075	5.874	4.102	2.198	5.3	2.05
1" Union Replacement Gasket	A5400012	1.181	1.181	0.118	-	0

## L'installation

Refer to the Uponor Thermal Actuator Instruction Sheet for additional information.

## Applications connexes

Radiant Heating and Cooling Systems  
Permafrost Protection Systems  
Turf Conditioning Systems

## Les codes

-	ASSE 1016-T ASSE 1017
---	-----------------------

## Annonces

-

## Remarques :

Connections:  
3/4" sweat; 1" sweat  
Operating voltage 24VAC nominal, 1 watt  
Time to open/close 3 to 5 minutes  
End switch rating 24VAC, 2A resistive

## Notes de bas de page

-

## Coordonnées de la personne-ressource

Uponor Inc.  
5925 148th Street West  
Apple Valley, MN 55124  
T 800.321.4739  
F 952.891.2008

Uponor Ltd.  
6510 Kennedy Road  
Mississauga, ON L5T 2X4  
T 888.594.7726  
F 800.638.9517