

Ensembles TruFLOW Jr. avec vannes d'équilibrage et collecteurs sans vanne



Renseignements sur le projet


Nom du poste :	Lieu :
Ingénieur :	Date de soumission:
Entrepreneur :	Présentée par:
Représentant du fabricant :	Approuvé par :

Données techniques

Material	Brass
Manifold size	1 inch
Loop Cv	1.9 Cv
End type 1	ISO 228-G 1-1/4"
End type 2	ISO 228-G 3/4"
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)
Max. fluid flow rate	14 gpm
Prop 65 label required?	Yes

Informations sur le produit et utilisation de l'application

The TruFLOW™ Jr. Assembly with Balancing Valves and Valveless is fully assembled and ready for installation. Use the TruFLOW Balancing Hex Key on the internal balancing valves of the supply manifold to balance the loops across the manifold. The manifold body ends have R32 unions, and the loop outlets have R20 male threads.



Nom de la pièce	Número de pièce	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	F [mm]	G [mm]	H [mm]	Weight per UOM [kg/UOM]
TruFLOW Jr. Assembly, Balancing Valves and Valveless, 2-loop	A2660200	182.51	285.41	74.14	50	50.51	32.64	51.14	46.99	2.359
TruFLOW Jr. Assembly, Balancing Valves and Valveless, 3-loop	A2660300	232.51	285.41	74.14	50	50.51	32.64	51.14	50.01	2.3405
TruFLOW Jr. Assembly, Balancing Valves and Valveless, 5-loop	A2660500	332.51	285.41	74.14	50	50.51	32.64	51.14	150.01	4.5223
TruFLOW Jr. Assembly, Balancing Valves and Valveless, 6-loop	A2660600	382.51	285.41	74.14	50	50.51	32.64	51.14	200.03	5.806
TruFLOW Jr. Assembly, Balancing Valves and Valveless, 7-loop	A2660700	432.51	285.41	74.14	50	50.51	32.64	51.14	250.01	6.396
TruFLOW Jr. Assembly, Balancing Valves and Valveless, 8-loop	A2660800	482.51	285.41	74.14	50	50.51	32.64	51.14	300	6.895

Nom de la pièce	Número de pièce	Les codes	Normes	Annonces
Ensembles TruFLOW Jr. avec vannes d'équilibrage et collecteurs sans vanne	All	IMC IRC NBC of Canada UMC	CSA B137.5 R32: ISO 228-G 1 1/4" ASTM F877 R20: ISO 228-G 3/4"	cNSFus-rfh

L'installation

TruFLOW Jr. Manifolds are fully assembled ready for installation. The TruFLOW Balancing Hex Key is used on the internal balancing valves of the supply manifold. Refer to the Uponor TruFLOW Jr. Manifold Instruction Sheet for further information.

Applications connexes

- Radiant Heating and Cooling Systems
- Permafrost Prevention Systems
- Turf Conditioning Systems

Remarques :

Manifold body threaded connections: R32
Manifold loop threaded connections: R20

Notes de bas de page

Coordonnées de la personne-ressource

-	Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008	Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517
---	---	---