

Accessoires PROPEX pour gicleur d'incendie ProPEX en laiton sans plomb (LF)



Submittal information

Date de soumission:

Project Information

Job name : Location :

Engineer : Date de soumission:

Contractor : Présentée par:

Manufacturer's representative : Approved by :

Technical Data

End type 1 ProPEX 1/2"
 Temp./pressure ratings 73°F (23°C) at 160 psi (11 bar)
 180°F (82°C) at 100 psi (6.9 bar)
 200°F (93°C) at 80 psi (5.5 bar)



Part name	Part no.	A [inch]	B [inch]	C [inch]	Weight per UOM [lbs/UOM]	Equivalent length branch [ft]	Material
Fire Sprinkler Adapter Mounting Bracket, 3/4" and 1"	A7750700	3.171	2.484	1.839	0.17	-	Metal
Fire Sprinkler Adapter Push-on Nut, 25/pkg.	F7000005	2.125	0.233	2.125	0.01	0	Steel
Screws, #10 x 1 1/2", Pan Head, Full Thread, 100/pkg.	F7001500	-	-	-	-	-	-

Installation Related applications

- AquaSAFE™ Fire Safety Systems

Codes Standards Listings

- UL 1821

Trademark Information

ProPEX® is a registered trademark of Uponor Inc. ProPEX™ is a trademark of Uponor Ltd.

Contact information

Uponor Inc.
 5925 148th Street West
 Apple Valley, MN 55124
 T 800.321.4739
 F 952.891.2008

Uponor Ltd.
 6510 Kennedy Road
 Mississauga, ON L5T 2X4
 T 888.594.7726
 F 800.636.9517