

Collecteurs à vanne en cuivre avec vannes à bille filetées R20/R25



Renseignements sur le projet

Nom du poste :	Lieu :
Ingénieur :	Date de soumission:
Entrepreneur :	Présentée par:
Représentant du fabricant :	Approuvé par :

Données techniques

Material	Copper
Manifold size	2 inch
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar) 210 °F (99 °C) at 149 psi (10.3 bar)
Max. fluid flow rate	45 gpm
Prop 65 label required?	Yes



Informations sur le produit et utilisation de l'application

The 2" x 4' Copper Valved Manifold with R20/R25 Threaded Ball Valves is designed for radiant heating applications. The manifold has a 2" copper sweat fitting adapter supply connection and 3/4" nominal branches that are 4 inches on center. This 12-outlet manifold comes preassembled with R20 and R25 threaded ball valve connections.

Nom de la pièce	Numéro de pièce	A [mm]	B [mm]	C [mm]	Cv	End Type 1	Weight per UOM [kg/UOM]
2" x 4' Copper Valved Manifold with R20 Threaded Ball Valves, 12 outlets	F2811220	1219.20	145.48	58.89	7	ISO 228-G 3/4"	6.691
2" x 4' Copper Valved Manifold with R25 Threaded Ball Valves, 12 outlets	F2811225	1219.20	147.48	58.89	7.3	ISO 228-G 1"	7.258

Nom de la pièce	Numéro de pièce	Les codes	Normes	Annonces
Collecteurs à vanne en cuivre avec vannes à bille filetées R20/R25	All	-	CSA B125 CSA B137.5 ASTM F877	cNSFus-rfh

L'installation	Applications connexes
Install using any product designed to mount 2" copper pipe as a mounting bracket. Refer to the Uponor Radiant Floor Heating Installation Handbook for additional information.	Radiant Heating and Cooling Systems Permafrost Protection Systems Turf Conditioning Systems

Remarques :

Ball Cv for the R20 outlet:
7.00
Ball Cv for the R25 outlet: 7.30

Notes de bas de page	Coordonnées de la personne-ressource
-	Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008 Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517