

Supports de tuyau pour PEX-a

Renseignements sur le projet

Nom du poste :	Lieu :
Ingénieur :	Date de soumission:
Entrepreneur :	Présentée par:
Représentant du fabricant :	Approuvé par :

Informations sur le produit et utilisation de l'application

PEX-a Pipe Support is a non-combustible, self-gripping, galvanized-steel channel for crosslinked polyethylene (PEX-a) pipe. It provides continuous, uninterrupted support of PEX-a pipe, allowing hanger placement similar to that of metallic pipe. Use PEX-a Pipe Support in conjunction with un-insulated Uponor AquaPEX® or Wirsbo hePEX™ PEX-a pipe in ASTM E84 plenum applications. The PEX-a pipe with pipe support can be insulated with typical CTS (copper tube size) pipe insulation. PEX-a Pipe Support is offered in 9-foot lengths and comes with nylon-coated, stainless-steel strapping.



Nom de la pièce	Numéro de pièce	A [mm]	B [mm]	C [mm]	Material group	Subcomponent Material	Prop 65 label required?	Weight per UOM [kg/UOM]
1/2" PEX-a Pipe Support, 9-ft. length	F7040500	2743.20	17.20	10.31	Metal	Commercial-grade (Type B) galvanized steel	-	0.4989522004
3/4" PEX-a Pipe Support, 9-ft. length	F7040750	2743.20	23.39	14.02	Metal	Commercial-grade (Type B) galvanized steel	No	0.6803893642
1" PEX-a Pipe Support, 9-ft. length	F7041000	2743.20	29.54	17.73	Metal	Commercial-grade (Type B) galvanized steel	-	0.866362457
1 1/4" PEX-a Pipe Support, 9-ft. length	F7041250	2743.20	35.46	21.26	Metal	Commercial-grade (Type B) galvanized steel	-	0.9525451098
1 1/2" PEX-a Pipe Support, 9-ft. length	F7041500	2743.20	41.22	24.71	Metal	Commercial-grade (Type B) galvanized steel	-	1.133982274
2" PEX-a Pipe Support, 9-ft. length	F7042000	2743.20	53.21	31.90	Metal	Commercial-grade (Type B) galvanized steel	-	1.632934474
2 1/2" PEX-a Pipe Support, 9-ft. length	F7042500	2743.20	65.07	39.04	Metal	Commercial-grade (Type B) galvanized steel	-	2.086527383
PEX-a Pipe Support Strapping for 1/2", 3/4" and 1" PEX	Q7410510	-	-	-	Plastic	-	-	0.0018
3" PEX-a Pipe Support, 9-ft. length	F7043000	2743.20	76.81	45.97	Metal	Commercial-grade (Type B) galvanized steel	-	2.812276039
PEX-a Pipe Support Strapping for 1 1/4", 1 1/2" and 2" PEX	Q7411220	-	-	-	Plastic	-	-	0.0036
PEX-a Pipe Support Strapping for 2 1/2", 3", 3 1/2" PEX	Q7412540	-	-	-	Plastic	-	-	0.0059

Nom de la pièce	Numéro de pièce	Les codes	Normes	Annonces
Supports de tuyau pour PEX-a	All	IMC UMC	ASTM E84	QAI P321 (up to 3")

L'installation	Applications connexes
Install PEX-a Pipe Support vertically or horizontally for plenum and non-plenum applications. Refer to the Uponor PEX-a Pipe Support Instruction Sheet for installation guidelines.	PEX-a Plumbing Systems Radiant Heating and Cooling Systems AquaSAFE™ Fire Safety Systems

Notes de bas de page		Coordonnées de la personne-ressource	
-		Uponor Inc.	Uponor Ltd.
		5925 148th Street West	6510 Kennedy Road
		Apple Valley, MN 55124	Mississauga, ON L5T 2X4
		T 800.321.4739	T 888.594.7726
		F 952.891.2008	F 800.638.9517