

Attaches pour PEX

Renseignements sur le projet


Nom du poste :	Lieu :
Ingénieur :	Date de soumission:
Entrepreneur :	Présentée par:
Représentant du fabricant :	Approuvé par :

Données techniques

Material	Plastic
Subcomponent Material	Nylon

Informations sur le produit et utilisation de l'application

Uponor PEX Clips are designed to suspend crosslinked polyethylene (PEX) tubing below the underside of a subfloor in a joist cavity installation.



Nom de la pièce	Numéro de pièce	A [mm]	B [mm]	C [mm]	Prop 65 label required?	Weight per UOM [kg/UOM]
3/8" PEX Clip, 100/pkg.	F7060375	17.40	28.95	40.97	-	0.0068038936
1/2" PEX Clip, 100/pkg.	F7051258	17.40	28.95	42.56	-	0.0072574866
3/4" PEX Clip, 100/pkg.	F7057500	17.40	35.20	48.56	Yes	0.0081646724
1" PEX Clip, 50/pkg.	F7051001	17.40	44.95	55.93	Yes	0.013

L'installation	Applications connexes
Mount the PEX Clips to the underside of the subfloor in the joist cavity with the use of a drywall screw or nail. Secure the tubing to the clips at 36" intervals along the joist cavity. Refer to the Uponor Radiant Installation Handbook for additional information.	Radiant Heating and Cooling Systems

Notes de bas de page	Coordonnées de la personne-ressource
-	Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008 Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517